



[Home \(/\)](#) > [Products \(/product/\)](#) > [SIP Intercom \(/proa/\)](#) > [Akuvox R27A IP Video](#)



Akuvox R27A IP Video Intercom

Tel

Message

Contact Us

Home

• High quality video quality

• Real-time entrance monitoring

- Remote door opening
- RF card reader and numeric keypad
- SIP/ONVIF/Wiegand/PoE/IP65

Online Inquiry

Description

R27A is a fashionable, SIP-enabled IP video door phone with a RF card reader and a numeric keypad. It enables easy monitoring of an entrance area and convenient entry control. The ability of granting or denying access based on talking to and seeing your visitors as if in person, gives one a true sense of security and great peace of mind.

Physical Features

Body material: aluminum panel
Camera: 3M pixels, with automatic lighting
Button: manager center, dial key and clear key
Keypad: numeric keypad
RF card reader: 13.56MHz and 125 kHz
PoE IEEE802.3af
Power consumption: 12V DC input, <12W
G-sensor for tamper alarm
Support infrared sensor
Enclosure rating: IP65
Installation: flush mounting or wall-mounting
Dimensions: 280x130x68mm

Interface Features

1xRJ45 10/100M Mbps Ethernet port
Output relay: 3 output relays for door opener
Relays controlled individually by DTMF tones
RS485 port
Wiegand port

SIP Features

SIP v1 (RFC2543), SIP v2 (RFC3261)
Line: 2 SIP accounts
Akuvox
Open A Smart World

Audio Features

1 built-in microphone with IP67 rating
2W speaker with IP66 rating
Codec: G.711a, G.711 μ , G.722 and G.729
Speech quality: 7 kHz
Echo cancellation
Voice activity detection
Comfort noise generator

Video Features

Resolution: up to 720p
Image transfer rate: 720p@30fps max.
Camera permanently operational
Auto-night mode with LED illumination
Illumination: 0.1LUX min.
Auto white balance
Internal light sensor: image lighting during dark hours
Codec: H.264, MPEG-4 and MJPEG
Support live stream and RTSP
Compliance with ONVIF

Network Features

Static IP or DHCP
802.1Q VLAN
NTP for auto time setting

Administration Features

Auto-provisioning: FTP/TFTP/HTTP/HTTPS/PnP/DHCP
Configuration management: web-based management or auto provisioning
TR069
SNMP

Application Scenarios

Office door phone with on-site or hosted IP-PBX
Perfect for apartment/flat intercom with door access control
Control remote site entry over the internet

Online Inquiry

Akuvox

Open A Smart World

Name	Phone	E-mail *
Content *		
Code		Submit

Previous: [Akuvox R29F Smart Intercom \(/proa/e1175589-05be-1e40-bc43-4c88758895e5.shtml\)](/proa/e1175589-05be-1e40-bc43-4c88758895e5.shtml)

Next: [Akuvox R26C IP Video Intercom \(/proa/pro3.shtml\)](/proa/pro3.shtml)

Copyright©AKUVOX All rights reserved. [Sitemap \(/map.shtml\)](/map.shtml)

