

T21P E2

HD Voice: HD Codec, HD speaker, HD handset

132 x 64-pixel graphical backlit LCD

2 VoIP accounts

Dual 10/100 Ethernet Ports, integrated PoE

Full Duplex speakerphone

Headset Port

Wall mountable

XML/LDAP remote phonebook



Entry-level IP Phone with 2 Lines & HD Voice voice

Yealink's T21P E2 takes entry-level IP phones to a level never achieved before. Making full use of high quality materials, plus an extra large 132 x 64 pixel graphical LCD showing a clear 5 line data display, it offers a smoother user experience, much more visual information at a glance plus full support for HD voice. Dual10/100 Mbps network ports, with integrated PoE for extended network use.

The T21P E2 supports two VoIP accounts, simple, flexible and secure installation options, plus support for IPv6, Open VPN and back-up redundancy server. It also operates with SRTP/HTTPS/TLS. 802.1x. As a very cost-effective and powerful IP phone, the T21P E2 maximises productivity in both small and large office environments.

T21P E2

Audio Features

Full-duplex hands-free speakerphone with AEC
 Codecs: G.722(Wideband), G.711(A/μ), G.723, G.729AB, G.726
 DTMF: In-band, Out-of-band(RFC 2833) and SIP INFO
 VAD, CNG, AEC, PLC, AJB, AGC

Phone Features

2 VoIP accounts
 Call hold, mute, DND,
 One-touch speed dial, hotline
 Redial, call return, auto answer
 Call forward, call waiting, call transfer
 Group listening, SMS
 Local 3-way conferencing
 Direct IP call without SIP proxy
 Ring tone selection/import/delete
 Keypad lock, emergency call
 Set date time manually or automatically
 URL & Action URI
 > Dial Plan
 > XML Browser
 > Action URL & Action URI

Directory

Local phonebook up to 1000 entries
 Black list
 XML/LDAP remote phonebook
 Intelligent search method
 Phonebook search/import/export
 Call history: dialled/received/missed/forwarded

IP-PBX Features

Anonymous call, anonymous call rejection
 Message waiting indicator (MWI)
 Voice mail, call park, call pickup
 Intercom, paging, music on hold
 Call completion, call recording, hot-desking

Display and Indicator

132x64-pixel graphical LCD back-light
 LED for call and message waiting indication
 Intuitive user interface with icons and soft keys
 National language selection
 Caller ID with name, number

Physical Features

2xRJ45 10/100M Ethernet ports
 31 keys including 4 soft keys
 4 LEDs: 1 x power, 2 x line, 1 x message
 1xRJ9 handset port
 1xRJ9 headset port
 Wall-mountable
 Optional power adapter: AC 100~240V input and DC 5V/600mA Output
 Power over Ethernet (IEEE 802.3af)
 Power consumption: 1.8-2.3W
 Net weight: 0.81kg
 Dimension: 209mm*188mm*150mm*41mm
 Operating humidity: 10~95%
 Storage temperature: -10~50°C

Management

Configuration: browser/phone/auto-provision/RPS support
 Auto provision via FTP/TFT P/HTTP/HTTPS for mass deployment
 Auto-provision with PnP
 Zero-sp-touch
 Provisioning server redundancy supported
 Reset to factory, reboot
 Package tracing export, system log

Network and Security

SIP v1 (RFC2543), v2 (RFC3261)
 IPv6 open VPN
 NAT transverse: STUN mode
 Proxy mode and peer-to-peer SIP link mode
 IP assignment: static/DHCP /PPPoE
 HTTP/HTTPS web server
 Time and date synchronization using SNTP
 UDP/TCP/DNS-SRV(RFC 3263)
 QoS: 802.1p/Q tagging (VLAN), Layer 3 ToS, DSCP
 SRTP for voice
 Transport Layer Security (T LS)
 HTTPS certificate manager
 AES encryption for configuration file
 Digest authentication using MD5/MD5- sess
 IEEE802.1X

Packaging

Qty/CTN: 11.7KG
 N.W/CTN: 12.5KG
 G.W/CTN: 12.3KG
 Giftbox size: 215mm*200mm*118mm
 Carton Meas: 615mm*436mm*208mm


Certifications



WEEE Compliant



RoHS Compliant



Yealink

EASY VoIP