

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION:

Kemsol STAIN-SOLVE

CHEMICAL SOLUTIONS LTD

1 Freight Place
Airport Oaks
Auckland 2022
New Zealand.

Solvent spotter for laundry stain removal.
MPI Approved C33 (all animal product except dairy)

PO Box 107-105, Auckland Airport 2150, Auckland, New Zealand.

Phone: (64-9) 255-5609

Fax: (64-9) 255-5610

E-mail: sales@kemsol.co.nz

Website: www.kemsol.co.nz

EMERGENCY CONTACT: Phone (64-9) 255-5609 8 am to 5 pm Mon to Fri
After Hours: National Poisons & Hazardous Chemical Information Centre: 0800-764-766 (0800-POISON)

2. HAZARD IDENTIFICATION:

This material is hazardous according to the EPA Minimum Degrees of Hazard and Classification Notices 2017.

3.1C Flammable liquid and vapour.

6.1E May be harmful if swallowed and enters airways.

Cleaning Products Flammable Group Standard HSR No: 002528

6.1E May be harmful if swallowed.

6.3B Causes mild skin irritation.

6.4A Causes eye irritation.

9.1B Toxic to aquatic life with long lasting effects.

COMPOSITION/INFORMATION ON INGREDIENTS:

Aliphatic hydrocarbon solvents	> 50 %
D Limonene (CAS# 68647-72-3)	2 – 10 %
N-Butyl Acetate (CAS #123-86-4)	2 – 10 %
Dipropylene Glycol Monomethyl Ether (CAS # 34590-94-8)	2 – 10 %
Surfactants	2 - 10 %

4. FIRST AID MEASURES:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN OR HAIR: Remove immediately all contaminated clothing. Rinse skin with water. If skin irritation occurs: Get medical advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

MEDICAL ASSISTANCE: IF exposed or concerned get medical advice/ attention. Call your nearest Medical Centre or the NZ National Poisons Centre 0800-764-766 for advice. Have this label or Safety Data Sheet on hand.

5. FIRE FIGHTING MEASURES:

This product will form flammable mixtures with air when vapourised. Isolate or avoid ignition sources (electrical and fire).

Containers subject to heat from a fire may explode scattering burning contents. Where possible remove containers from the path of the fire.

Otherwise cool with water spray to avoid heating.

Firefighters wear SCBA and chemical resistant suits.

Foam, CO₂, or chemical dry powder to extinguish a local fire. Water spray on large fires only. No water jets.

6. ACCIDENTAL RELEASE MEASURES:

Spills on floors will produce a slippery surface. Shut off, or isolate, all possible sources of ignition.

Do not allow any spills, original or diluted, to enter wastewater drains. If material does enter, alert the local drainage authorities.

Contain minor (less than 100 litres) from local drainage with any suitable bund or barrier. Where possible dilute with water (water soluble products only) and contain the resulting solution. Then clean up with mops or any suitable absorbant inert material such as Mineral

Sponge, paper, rags, sand, or soil. Pack absorbed waste material into drums, which can be closed, for waste disposal.

Large spills from drums should be contained from drains and diluted with water where possible. Alert the local Fire Brigade.

Collect absorbed material in open-top drums which can be closed and sent to landfill.

7. HANDLING AND STORAGE:

Precautions for Safe Handling:

Read label before use. Keep away from heat, open flames and hot surfaces. No smoking. Keep container tightly closed. Ground container and receiving equipment. Use explosion-proof electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wear protective gloves, protective clothing and eye protection/face protection. Keep out of reach of children. Wash hands thoroughly after handling. Avoid release to the environment.

Precautions for Safe Storage:

Store drums and carboys with secure closures, in sites where they can be kept cool and away from heat and ignition sources.

Storage in HSNO defined Hazardous Substance Locations and Transit Depots is required for Class 3.1C products where greater than 500 litres is stored in 20 litre carboys and 200 litre drums, and greater than 1500 litres is stored in 5 litre jerries.

Handle to prevent damage to containers. Should packaging be damaged, repack into clean and dry containers of the same type and mark the product name carefully on the container.
Always replace lids and caps after using the product. Return all packages to safe storage as soon as possible after use.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION:

Exposure controls: No data is available for the product.

- Aliphatic hydrocarbon solvents - supplier's recommendation WES-TWA 143ppm
- D Limonene - supplier's SDS WES-TWA 100ppm
- N-Butyl Acetate - WES-TWA 150ppm WES-STEL 200 ppm
- Propylene Glycol Monomethyl Ether - WES-TWA 100ppm WES-STEL 150 ppm

Eye protection: Safety glasses.

Protective clothing: Chemically impregnable gloves, work shoes, protective work clothes (an apron or overalls).

Respiratory protection: Not required for the regular use of this product. If the liquid is being sprayed or vaporised, a face shield and/or respirator must be worn. These operations should be carried out by trained personnel only.

Ventilation: Where spraying or vaporising is being carried out, ensure there is ready access to eyewash units and safety shower. Also adequate ventilation is provided in the work space.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance	Clear uncoloured liquid
Odour	Sweet fruity
pH	Not applicable
Flash Point	50° C
Ignition Point	> 400 ° C
Specific Gravity	0.82
Refractive Index	56 %Bx
Viscosity	Not applicable
Foam	Not applicable
Solubility in water	Emulsifies in water

STABILITY AND REACTIVITY:

The product is considered stable in normal storage and use. Evaporation will occur if exposed to air.
Avoid contamination with oxidising substances. Hazardous polymerisation will not occur. Combustion will release oxides of carbon.

11. TOXICOLOGICAL INFORMATION:

No data is available for the product.

12. ECOLOGICAL INFORMATION:

No data is available for the product.

13. DISPOSAL CONSIDERATIONS:

Dispose of in accordance with local regulations by recognised waste disposal experts. Incineration is the preferred method.
Spilled liquids must be absorbed by neutral materials such as Mineral Sponge, paper, rags, sand, or soil and packed in containers which can be sealed and sent to land fill or incineration.
Large spills will require suctioning into suitable tanks, and if not recoverable, disposed of through recognised waste disposal experts.
Used containers should be rinsed, not recycled, but disposed of in landfill or incinerated.

14. HSR NO. :

NZ Land Transport Rule: Dangerous Goods Rule 2005	Classified as Dangerous Goods for Land Transport in New Zealand.
UN Number:	1268
Dangerous Goods Class:	3
Proper Shipping Name:	Petroleum Distillates NOS
Hazchem Group:	3Y
Packing Group:	III

NZ REGULATORY INFORMATION:

This material is hazardous according to the EPA Minimum Degrees of Hazard and Classification Notices 2017.
Cleaning Products Flammable Group Standard HSR No: 002552.
HSNO Act Controls Regulations 2001 for Stain-Solve
Limit and monitor exposure during the use of the product Make use of suitable equipment for handling the product
Wear suitable protective clothing while being used Do not expose product to any form of ignition source

OTHER INFORMATION:

Formulation reference and version number: R11-100
This SDS was prepared from data available on 05 July 2018
This SDS was printed on 9 August 2018.
This SDS will be reviewed no later than 31 August 2021

END OF THIS SAFETY DATA SHEET