

Page 1 of 6 **BTI-027**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.5

SDS Revision Date: 02/21/2017

1.1	Product Name:	ANTIQUE BLACK® GEL
1.2	Chemical Name:	Acid Mixture
1.3	Synonyms:	750350, 750351, 750358
1.4	Trade Names:	Antique Black® Gel
1.5	Product Use:	Blackening Solution for Brass & Copper
1.6	Distributor's Name:	Sculpt Nouveau, LLC
1.7	Distributor's Address:	1155 Industrial Ave. Escondido, CA 92029
1.8	Emergency Phone:	ChemTrec +1 (800) 424-9300/+1 (703) 527-3887 or Poison Control Center +1 (855) 281-1742
1.9	Business Phone / Fax:	+1 (760) 432-8242

This product is classified as a hazardous substance and as dangerous goods according to the

classification criteria of [NOHSC: 1088 (2004)] and ADG Code (Australia). DANGER! TOXIC IF SWALLOWED. MAY CAUSE SEVERE SKIN BURNS OR EYE DAMAGE. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. MAY INTENSIFY FIRE; OXIDIZER. Hazard Statements (H): H301 - Toxic if swallowed. H314 - Causes severe skin burns and eye damage. H373 - May cause damage to organs through prolonged or repeated exposure. H272 -May intensify fire; oxidizer. H410 – Very toxic to aquatic life with long lasting effects. Precautionary Statements (P): P220 - Keep/Store away from clothing/ combustible materials. P273 - Avoid release to the environment. P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 - Dispose of

contents/ container to an approved waste disposal plant.



3. COMPOSITION & INGREDIENT INFORMATION

								EXPO	SURE LI	MITS IN	AIR (mg	g/m³)	
				ACGIH ppm		NOHSC		OSHA					
							ppm		ppm				
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	TLV	STEL	ES- TWA	ES- STEL	ES- PEAK	TLV	STEL	IDLH	OTHER
WATER	7732-18-5	ZC0110000	231-791-2	60-100	NE	NE	NF	NF	NF	NE	NE	NE	
WATER													
POLYOXYETHYLENE STEARYL WAX	9005-00-9	NA	500-017-8	7-13	NA	NA	NF	NF	NF	NA	NA	NA	
DERIVATIVES													
COPPER (II) NITRATE, TRIHYDRATE	10031-43-3	GI7875000	221-838-5	1-5	(1)	NA	NF	NF	NF	(1)	NA	NA	
COPPER (II) NITRATE, TRIHTDRATE	Metal Corrosion 1; Skin Corrosion1B; H290, H314												
SELENIOUS ACID	7783-00-8	VS7175000	231-974-7	1-5	(0.2)	NA	(0.2)	NF	NF	(0.2)	NA	NA	
SELENIOUS ACID	Acute Toxicity-Inh 3; Acute Toxicity-Oral 3; STOT-Repeated Exp 2; Acute Aquatic Toxicity 1; Chronic Aquatic Toxicity 1); H301, H331												
NITRIC ACID	7697-37-2	QU5775000	231-714-2	1-5	2	4	2	NF	NF	2	NA	25	
NT RIC ACID	Oxidizing Liquid 3	3; Skin Corrosion 1A	; H272, H314										
PHOSPHORIC ACID	7664-38-2	TB6300000	231-633-2	1-5	(1)	(3)	NF	NF	NF	NA	NA	1000	
FROSFRORIC ACID	Metal Corrosion	I; Skin Corrosion1B;	H290, H314										

4. FIRST AID MEASURES

4.1	First Aid:	Ingestion:	Do not induce vomiting. Call +1 (855) 281-1742 for emergency medical advice. If vomiting occurs, keep victim's head lowered (forward) to keep vomit from entering the lungs. Call 911 for emergency medical transport if any symptoms noted.
		Eyes:	Remove and discard contact lenses if worn and flush eyes with large amounts of water for at least 20 minutes. Seek immediate medical attention when done rinsing eyes.
		Skin:	Remove contaminated clothing and wash exposed skin with large amounts of soap and water. Seek medical attention if any blistering, swelling or open sores develop.
		Inhalation:	Move victim to fresh air. Contact emergency medical services (911) if any difficulty in breathing occurs or if victim loses consciousness.
4.2	Effects of Exposure:	Eyes:	Severe or permanent eye damage.
		Skin:	Burns upon direct contact.
		Ingestion:	Severe burns of mouth, throat, stomach.
		Inhalation:	Severe irritation or burns in respiratory tract and mucous membranes. Possible lung damage.
4.3	Symptoms of Overexposure:	Eyes:	Redness, burning, irritation, and swelling around eyes
		Skin:	Redness, burning, itching, rash, blistering of skin.
		Ingestion:	Nausea, vomiting, severe abdominal pain.
1		Inhalation:	Coughing, wheezing, swelling of throat, irritation in mucous membranes, difficulty breathing.



7.3

Special Precautions:

SAFETY DATA SHEET

Page 2 of 6 **BTI-027**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.5 SDS Revision Date: 02/21/2017 4. FIRST AID MEASURES - cont'd 4.4 Acute Health Effects: May be harmful if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. May be harmful if swallowed. Causes burns. May be harmful if absorbed through skin 4.5 Chronic Health Effects: May damage the nervous system, kidney and/or liver. 4 6 Target Organs: Eyes, skin, nervous system, kidneys, liver, respiratory system. Medical Conditions 4.7 Pre-existing dermatitis, other skin conditions, and disorders of the **HEALTH** 3 Aggravated by Exposure: target organs (eyes, skin, and respiratory system) or impaired kidney **FLAMMABILITY** 0 function may be more susceptible to the effects of this substance. PHYSICAL HAZARDS 2 PROTECTIVE EQUIPMENT Н **EYES** SKIN LUNGS 4.8 Notes to Physician: This product contains Selenious Acid and is potentially fatal if ingested even in small amounts. 24-hour admission should be considered in asymptomatic or minimally symptomatic patients as delayed toxic effects including pulmonary edema and multi-organ failure may occur. 24/7 medical toxicology consultation is available at +1 (855) 281-1742. 5. FIREFIGHTING MEASURES Fire & Explosion Hazards: Non-flammable. May react with metals to release hydrogen gas, which can form explosive mixtures with air. May intensity fire; oxidizer. Extinguishing Methods: 5.2 Use fire-extinguishing media appropriate for surrounding materials. Firefighting Procedures: 5.3 As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Fight fires as for surrounding materials. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, phosphorous, selenium and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. 6. ACCIDENTAL RELEASE MEASURES Spills Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE). Use safety glasses or safety goggles and face shield, use gloves and other protective clothing (e.g., apron, boots, etc.) to prevent skin contact. Small Spills: Wear appropriate protective equipment including gloves and protective eyewear. Use a non-combustible, inert material such as vermiculite or sand to soak up the product and place into a container for later disposal. Large Spills: Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant. Recover as much free liquid as possible and collect in acid-resistant container. Use absorbent to pick up residue. Avoid discharging liquid directly into a sewer or surface waters. 7. HANDLING & STORAGE INFORMATION 7 1 Work & Hygiene Practices: Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame. Use only in ventilated areas. Keep out of the reach of children. Immediately clean-up and decontaminate any spills or residues. Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct 7.2 Storage & Handling: sunlight. Store in acid-resistant containers. Keep containers covered when not in use. Avoid temperatures above 40°C (120°F). Keep away from incompatible substances (see Section 10). Protect containers from physical damage.

Empty containers may retain hazardous product residues.



Page 3 of 6 **BTI-027**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.5

SDS Revision Date: 02/21/2017

8.1 8.2 8.3 8.4 8.5	Ventilation & Engineering Controls: Respiratory Protection:	8. EXPOSURE CONTROLS & PERSONAL PROTECTION Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eyewash station).
8.2 8.3 8.4	Controls:	handling of this product. Ensure appropriate decontamination equipment is available (e.g., sink, safety shower, eye-wash station).
8.3	Respiratory Protection:	
8.4		In instances where vapors or sprays of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.
	Eye Protection:	Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended.
8.5	Hand Protection:	Wear protective, chemical-resistant gloves (e.g., neoprene) when using or handling this product.
	Body Protection:	A chemical resistant apron and/or protective clothing are recommended when handling or using this product.
		9. PHYSICAL & CHEMICAL PROPERTIES
9.1	Appearance:	
9.1	Odor:	Viscous blue liquid Odorless
9.3	Odor Threshold:	
9.4	pH:	0.29 to 0.98 ppm (Nitric Acid)
9.5	Melting Point/Freezing Point:	1.35 NA
9.6	Initial Boiling Point/Boiling	
9.0	Range:	> 100 °C (> 212 °F)
9.7	Flashpoint:	Wax: 207 °C (405 °F) COC
9.8	Upper/Lower Flammability Limits:	NA NA
9.9	Vapor Pressure:	NA NA
9.10	Vapor Density:	<pre>< 1.0 (air = 1.0)</pre>
9.11	Relative Density:	1.10
9.12	Solubility:	Insoluble (water); Soluble (isopropanol)
9.13	Partition Coefficient (log Pow):	NA
9.14	Autoignition Temperature:	NA NA
9.15	Decomposition Temperature:	NA NA
9.16	Viscosity:	NA
9.17	Other Information:	Evaporation Rate: < 1.0 (ethyl ether = 1.0)
		10. STABILITY & REACTIVITY
10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Reaction with organics and strong reducing agents can produce organoselenides and hydrogen selenide. Thermal decomposition may produce selenium, nitrogen, phosphoric and copper oxides.
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Excessive heat, shock, friction.
10.5	Incompatible Substances:	Cyanides, water-reactive substances, strong reducing agents, chlorinated cleaners or sanitizers, combustible organic materials, most metals.
		11 TOYICOLOGICAL INFORMATION
44.4	Doutes of Enter:	11. TOXICOLOGICAL INFORMATION
11.1	Routes of Entry:	Inhalation: YES Absorption: YES Ingestion: YES
11.2	Toxicity Data:	Phosphoric Acid: LD ₅₀ (oral, rat) = 1530 mg/kg; Copper Nitrate Trihydrate: LD ₅₀ (oral, rat) = 794 mg/kg; LD ₅₀ (oral, rat) = 1030 mg/kg
11.3	Acute Toxicity:	See Section 2.4
11.4	Chronic Toxicity:	See Section 2.5
11.5	Suspected Carcinogen:	Components in this product are listed by IARC as Group 3 (Not classifiable as to its carcinogenicity to humans)
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.
ŀ	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.
ŀ	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.
	Reproductive Toxicity:	This product is not reported to cause reproductive effects in humans.
	Irritancy of Product:	See Section 2.3
11.7		
11.7	Biological Exposure Indices:	NE
	Biological Exposure Indices: Physician Recommendations:	NE Treat symptomatically.



Page 4 of 6 **BTI-027**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 02/21/2017 12. ECOLOGICAL INFORMATION 12.1 Environmental Stability: No data available. 122 Effects on Plants & Animals: No data available. 12.3 Effects on Aquatic Life: Very toxic to aquatic life with long lasting effects. Phosphoric Acid: EC₅₀ (Daphnia magna, 12h) = 4.6 mg/L 13. DISPOSAL CONSIDERATIONS 13.1 Waste Disposal: Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. 13.2 Special Considerations: U.S. EPA Hazardous Waste - Characteristic - Corrosive (D002), Characteristic - Toxic (D010) 14. TRANSPORTATION INFORMATION 49 CFR (GND): UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID, NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 5.0 L) IATA (AIR): 14 2 UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID, NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 0.5 L) 14.3 IMDG (OCN): UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID. NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 5.0 L) 14 4 TDGR (Canadian GND): UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID, NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 5.0 L) ADR/RID (EU): UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID, NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 5.0 L) 14.6 SCT (MEXICO): UN3264, LIQUIDOS, CORROSIVOS, ACIDO, INORGANICO, N.E.P. (ACIDO SELENIO, ACIDO NITRICO), 8, III, CANTIDAD LIMITADA (IP VOL ≤ 5.0 L) ADGR (AUS): UN3264, CORROSIVE LIQUIDS, ACIDIC, INORGANIC, N.O.S. (SELENIOUS ACID, NITRIC ACID), 8, III, LTD QTY (IP VOL ≤ 5.0 L) 15. REGULATORY INFORMATION 15.1 SARA Reporting Requirements: This product contains Nitric Acid, Phosphoric Acid and Selenious Acid, substances subject to SARA Title III, section 313 reporting requirements. 15.2 SARA Threshold Planning 302 TPQ (Nitric Acid): 1.000 lbs (454 kg) Quantity: 15.3 TSCA Inventory Status: The components of this product are listed on the TSCA Inventory. 15.4 **CERCLA Reportable Quantity** Selenious Acid: 10 lbs (4.54 kg); Nitric Acid: 1,000 lbs (454 kg); Phosphoric Acid: 5,000 lbs (2,270 kg) (RQ): 15.5 Other Federal Requirements: 15.6 Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class E (Corrosive Material). WHMIS Class D1 (Materials Causing Immediate and 15.7 State Regulatory Information: Selenious Acid is found on the following state criteria lists: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right-to-Know List (PA), and Wisconsin Hazardous Substances List (WI). Nitric Acid is found on the following state criteria lists: FL, MA, MN, New Jersey Right-to-Know List (NJ), PA, and Washington Permissible Exposures List (WA). Phosphoric Acid is found on the following state criteria lists: MA, PA. No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI) The primary components of this product are listed in Annex I of EU Directive 67/548/EEC. Other Requirements: Selenious Acid: Corrosive (C), Toxic (T). Risk Phrases (R): R35 - Causes severe burns. Safety Phrases (S): S1/2-7/9-24/25-26-28-46 - Keep locked up and out of the reach of children. Keep container tightly closed and in a well-ventilated place. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash with plenty of soap and warm water. If swallowed, seek medical advice immediately and show this container or label.



Page 5 of 6 **BTI-027**

SDS Revision: 1.5 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision Date: 02/21/2017 16. OTHER INFORMATION Other Information: DANGER! POISON. CORROSIVE. May be fatal if swallowed or harmful if inhaled. Causes severe burns to eyes and skin. OXIDIZER. Combustible materials that contact this product may ignite more easily and burn more intensely. Avoid shock, heat, and friction. Terms & Definitions: 16.2 See last page of this Safety Data Sheet. 16.3 Disclaimer: This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Birchwood Technologies' knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. Prepared for: **Birchwood Technologies** 7900 Fuller Road BIRCHWOOD Eden Prairie, MN 55344 USA Tel: +1 (952) 937-7900 TECHNOLOGIES Fax: +1 (952) 937-7979 http://www.birchwoodtechnologies.com Prepared by: ShipMate, Inc. P.O. Box 787

Training & Consulting

Sisters, Oregon 97759-0787 USA

Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700

http://www.shipmate.com



Page 6 of 6 **BTI-027**

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision Date: 02/21/2017

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No	Chemical Abstract Service Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists			
TLV	TLV Threshold Limit Value			
OSHA	OSHA U.S. Occupational Safety and Health Administration			
PEL	PEL Permissible Exposure Limit			
IDLH Immediately Dangerous to Life and Health				

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has
	stopped receives manual chest compressions and breathing to circulate blood
	and provide oxygen to the body

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS


HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH FLAMMABILITY PHYSICAL HAZARDS PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

Α			
В			
С	(Eller)	THE STATE OF THE S	
D	MAN		
Е	MAN		
F	(Ell)	THE N	





Splash Goggles









Protective Clothing Synthetic Apron & Full Suit





Dust & Vapor Half-Mask Respirator

Respirator

Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
ML	Maximum Limit
SCBA	Self-Contained Breathing Apparatus
Flam.	Flammable
Liq.	Liquid
Sol.	Solid
Tox.	Toxicity
Irrit.	Irritation
Sens.	Senitization
Ox.	Oxidizing
Corr.	Corrosion
Repr.	Reproductive (Harm)
Asp.	Aspiration
lnh.	Inhalation
Dam.	Damage
STOT SE	Specific Target Organ Toxicity – Single Exposure
STOT RE	Specific Target Organ Toxicity – Repeated Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABIL	FLAMMABILITY LIMITS IN AIR:					
Autoignitio	Minimum temperature required to initiate combustion in air with no other source					
Temperature	of ignition					
LEI						
	explode or ignite in the presence of an ignition source					
UEI	Upper Explosive Limit - highest percent of vapor in air, by volume, that will					
	explode or ignite in the presence of an ignition source					

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
₩	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
	S
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD _{Io}	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD _{io} , LD _{io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic effects
TC, TCo, LCio, & LCo	
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log K _{ow} or log K _{oc}	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System				
DOT	U.S. Department of Transportation				
TC	Transport Canada				
EPA	U.S. Environmental Protection Agency				
DSL	Canadian Domestic Substance List				
NDSL	Canadian Non-Domestic Substance List				
PSL	Canadian Priority Substances List				
TSCA	U.S. Toxic Substance Control Act				
EU	European Union (European Union Directive 67/548/EEC)				
WGK	Wassergefährdungsklassen (German Water Hazard Class)				

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

0	(4)	(4)		\odot	(1)		
Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

EC (67/548/EEC) INFORMATION:

		No.	*		®	×	×
С	E	F	N	0	Т	Xi	Xn
Corrosive	Explosive	Flammable	Harmful	Oxidizing	Toxic	Irritant	Harmful

CLP/GHS (1272/2008/EC) PICTOGRAMS:

			\Diamond			\		(1)
GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environ- ment