

# Clare Wall Paint - Perfect Eggshell



## Product Information

Our 100% acrylic, water-based formula applies easily and provides an even, uniform finish that resists dirt, grime, and mildew, while delivering exceptional performance, including washability, scrubability, durability...and all the abilities in between.

Our low-odor, Zero VOC\* paints are GREENGUARD Gold Certified, which means they meet the most stringent standards for low chemical emissions and support better indoor air quality.

*\*Zero VOC means no carbon-based solvents (volatile organic compounds) have been intentionally added to this product, although trace amounts of VOC may be present as residual components of other ingredients.*



## Prep

Proper prep is the secret to a flawless finish. To start, make sure your walls are clean, dry, and free from any dust, oil, mildew, wax, or other substances. If necessary, sand or scrape any loose or peeling paint. Repair any cracks, holes, or imperfections, and make sure surfaces are smooth and dusted clean before painting. We suggest dulling glossy surfaces with fine grit sandpaper to ensure proper adhesion.

Our paint is self-priming on most properly prepared surfaces, but if you're painting over a higher gloss finish or a darker color, we recommend using our multi-purpose primer first. For best results, always apply two coats of paint. For more information on how to prep for painting, visit: [www.clare.com/paintprep](http://www.clare.com/paintprep).

**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** 100% acrylic

**FINISH (ASTM D 523) EGGSHELL:** 10–15% on a 60° meter, 15–30% on a 85° meter

**COLORS:** See [www.clare.com/interiorcolors](http://www.clare.com/interiorcolors) for colors

**TINT BASES:** L Tintable White, M Medium, D Deep

**VISCOSITY AT 77°F/25°C (ASTM D 562):** 100–105 KU

**MAXIMUM VOC CONTENT:** 2 g/L (by ASTM Test Method D 6886)

**SOLIDS BY VOLUME (ASTM D 2697):** 40.0% ± 2%

**SOLIDS BY WEIGHT:** 54.2 ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 11.00 lbs

### COMPOSITION BY WEIGHT:

**PIGMENT:** 32.1%

**PRIME PIGMENTS\*:** 21.5

**REINFORCING PIGMENTS:** 10.6

**VEHICLE:** 67.9%

**ACRYLIC RESINS:** 20.7

**WATER & ADDITIVES:** 47.2

*\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.*

### RECOMMENDED FILM THICKNESS PER COAT:

**WET:** 3.7 mils

**DRY:** 1.5 mils

### PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS:

One gallon of Clare Wall Paint will cover 375–425 square feet depending on the condition of your wall or surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

**AVERAGE DRY TIME @ 77°F/25°C (ASTM D 1640):** Dries to the touch in 30–60 minutes. Recommended wait time between coats is 2–4 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One gallon containers, one quart containers.

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety).

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ; UL GREENGUARD Gold Certified

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**PRIMERS:** Clare Interior Multipurpose Primer

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/Safety](http://clare.com/Safety) or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead/or/asbestos](http://www.epa.gov/lead/or/asbestos), or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

Do not apply when the air or surface temperature is below 50°F.

**INGREDIENTS:** Water (07732-18-5), Rutile Titanium Dioxide (01317-80-2), Acrylic Resin (25586-20-3), Nepheline Syenite (37244-96-5), Silica, Amorphous Synthetic (07631-86-9), Aluminum Hydroxide (21645-51-2)

# Clare Trim Paint - Subtle Semi-Gloss



## Product Information

Our Trim Paint provides a remarkably durable finish that stands up to the toughest wear and tear including stains, fingerprints, and smudges. This 100% acrylic, water-based formula applies easily and delivers an even, uniform finish that resists dirt, grime, and mildew, while providing exceptional performance, including washability, scrubability, durability... and all the abilities in between.

Our low-odor, Zero VOC\* paints are GREENGUARD Gold Certified, which means they meet the most stringent standards for low chemical emissions and support better indoor air quality.

*\*Zero VOC means no carbon-based solvents (volatile organic compounds) have been intentionally added to this product, although trace amounts of VOC may be present as residual components of other ingredients.*



## Prep

Proper prep is the secret to a flawless finish. To start, make sure your walls are clean, dry, and free from any dust, oil, mildew, wax, or other substances. If necessary, sand or scrape any loose or peeling paint. Repair any cracks, holes, or imperfections, and make sure surfaces are smooth and dusted clean before painting. We suggest dulling glossy surfaces with fine grit sandpaper to ensure proper adhesion.

Our paint is self-priming on most properly prepared surfaces, but if you're painting over a higher gloss finish or a darker color, we recommend using our multi-purpose primer first. For best results, always apply two coats of paint. For more information on how to prep for painting, visit: [www.clare.com/paintprep](http://www.clare.com/paintprep).

**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** 100% acrylic

**FINISH (ASTM D 523) SEMI-GLOSS :** 40-50% on a 60° meter

**COLORS:** See [www.clare.com/interiorcolors](http://www.clare.com/interiorcolors) for colors

**TINT BASES:** L Tintable White, M Medium, D Deep

**VISCOSITY AT 77°F/25°C (ASTM D 562):** 100-105 KU

**MAXIMUM VOC CONTENT:** 2 g/L (by ASTM Test Method D 6886)

**SOLIDS BY VOLUME (ASTM D 2697):** 40.0% ± 2%

**SOLIDS BY WEIGHT:** 54.2 ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 10.79 lbs

### COMPOSITION BY WEIGHT:

**PIGMENT:** 28.4%

**PRIME PIGMENTS\*:** 21.9

**REINFORCING PIGMENTS:** 6.5

**VEHICLE:** 71.6%

**ACRYLIC RESINS:** 21.9

**WATER & ADDITIVES:** 49.7

*\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.*

### RECOMMENDED FILM THICKNESS PER COAT:

**WET:** 3.7 mils

**DRY:** 1.5 mils

### PRACTICAL COVERAGE PER COAT AT

**RECOMMENDED DRY FILM THICKNESS:** One gallon of Clare Trim Paint will cover 375-425 square feet depending on the condition of your wall or surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

### AVERAGE DRY TIME @ 77°F/25°C (ASTM D

**1640):** Dries to the touch in 30-60 minutes. Recommended wait time between coats is 2-4 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One gallon containers, one quart containers.

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety).

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ; UL GREENGUARD Gold Certified

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**PRIMERS:** Clare Interior Multipurpose Primer

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/Safety](http://clare.com/Safety) or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead/or/asbestos](http://www.epa.gov/lead/or/asbestos), or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

Do not apply when the air or surface temperature is below 50°F.

**INGREDIENTS:** Water (07732-18-5), Rutile Titanium Dioxide (01317-80-2), Acrylic Resin (25586-20-3), Barium Sulfate (07727-43-7), Silica, Amorphous Synthetic (07631-86-9), Fuller's Earth (08031-18-3), Aluminum Hydroxide (21645-51-2)

CLARE

CLARE, INC.  
246 5TH AVENUE, NEW YORK, NY 10001  
(646) 847-7746  
[WWW.CLARE.COM](http://WWW.CLARE.COM)

# Clare Ceiling Paint - Flat White



## Product Information

Designed for the easiest above-your-head application with minimal splatter, this acrylic, water-based formula delivers smooth, uniform coverage with exceptional hide to conceal flaws. The ultra-flat, non-reflective finish helps to maximize light while offering outstanding durability to resist dirt, grime, and mildew.

Our low-odor, Zero VOC\* paints are GREENGUARD Gold Certified, which means they meet the most stringent standards for low chemical emissions and support better indoor air quality.

*\*Zero VOC means no carbon-based solvents (volatile organic compounds) have been intentionally added to this product, although trace amounts of VOC may be present as residual components of other ingredients.*



## Prep

Proper prep is the secret to a flawless finish. To start, make sure your walls are clean, dry, and free from any dust, oil, mildew, wax, or other substances. If necessary, sand or scrape any loose or peeling paint. Repair any cracks, holes, or imperfections, and make sure surfaces are smooth and dusted clean before painting. We suggest dulling glossy surfaces with fine grit sandpaper to ensure proper adhesion.

Our paint is self-priming on most properly prepared surfaces, but if you're painting over a higher gloss finish or a darker color, we recommend using our multi-purpose primer first. For best results, always apply two coats of paint. For more information on how to prep for painting, visit: [www.clare.com/paintprep](http://www.clare.com/paintprep).

**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** Acrylic copolymer

**FINISH (ASTM D 523) FLAT:** 1.5-2.5% on a 60° meter, 1.0-2.0% on a 85° meter

**COLORS:** Snow Day (a versatile, bright white)

**VISCOSITY AT 77°F/25°C:** 100-110 KU

**MAXIMUM VOC CONTENT:** <5 g/L (by ASTM Test Method D 6886)

**SOLIDS BY VOLUME (ASTM D 2697):** 35.1% ± 2%

**SOLIDS BY WEIGHT:** 52.6% ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 11.60 lbs

**COMPOSITION BY WEIGHT:**

**PIGMENT:** 44%

**PRIME PIGMENTS\*:** 12.5

**REINFORCING PIGMENTS:** 31.5

**VEHICLE:** 56%

**ACRYLIC RESINS:** 5.9

**WATER & ADDITIVES:** 50.1

*\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.*

**RECOMMENDED FILM THICKNESS PER COAT:**

**WET:** 4.3 mils

**DRY:** 1.5 mils

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS:**

One gallon of Clare Ceiling Paint will cover 325-375 square feet depending on the condition of your wall or surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

**AVERAGE DRY TIME @ 77°F/25°C (ASTM D 1640):** Dries to the touch in 30-60 minutes. Recommended wait time between coats is 1-2 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety).

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ; UL GREENGUARD Gold Certified

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**PRIMERS:** Clare Interior/Exterior Primer

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/Safety](http://clare.com/Safety) or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead-or/asbestos](http://www.epa.gov/lead-or/asbestos), or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

Do not apply when the air or surface temperature is below 50°F.

**INGREDIENTS:** Ingredient (CAS #): Water (7732-18-5); Feldspar (68476-25-5); Titanium Dioxide (13463-67-7); Kaolin Calcined (92704-41-4); Copolymer Resin (Proprietary); Quartz (14808-60-7).

CLARE, INC.  
246 5TH AVENUE, NEW YORK, NY 10001  
(646) 847-7746  
[WWW.CLARE.COM](http://WWW.CLARE.COM)

CLARE

# Clare Interior/Exterior Primer



## Product Information

Our fast-drying, multi-surface acrylic primer blocks stains and seals your surface to ensure a smooth, uniform finish. This Zero VOC\*, low odor formula also delivers a long-lasting bond to a variety of interior and exterior surfaces including drywall, wood and masonry, as well as hard-to-stick surfaces, such as aged alkyd, aluminum, and galvanized metal.

Our low-odor, Zero VOC\* Primer is GREENGUARD Gold Certified, which means they meet the most stringent standards for low chemical emissions and support better indoor air quality.

*\* Zero VOC means no carbon-based solvents (volatile organic compounds) have been intentionally added to this product, although trace amounts of VOC may be present as residual components of other ingredients.*



## Prep

Proper prep is the secret to a flawless finish. To start, make sure your surface is clean, dry, and free from any dust, oil, mildew, wax, or other substances. If necessary, sand or scrape any loose or peeling paint. Repair any cracks, holes, or imperfections, and make sure surfaces are smooth and dusted clean before painting. We suggest dulling glossy surfaces with fine grit sandpaper to ensure proper adhesion. Our paint is self-priming on most properly prepared surfaces, but if you're painting over a higher gloss finish or a darker color, we recommend using our multi-purpose Primer first. For best results, always apply two coats of paint.

**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** Acrylic

**FINISH (ASTM D 523):** 2-8% on a 60° meter

**COLORS:** Stock white

**VISCOSITY AT 77°F/25°C:** 91-100 KU

**MAXIMUM VOC CONTENT:** 3 g/L (by ASTM Test Method D 6886)

**SOLIDS BY VOLUME (ASTM D 2697):** 36.2% ± 2%

**SOLIDS BY WEIGHT:** 50.0 ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 10.86 lbs

### COMPOSITION BY WEIGHT:

**PIGMENT:** 34.6%

**PRIME PIGMENTS\*:** 11.1

**REINFORCING PIGMENTS:** 23.5

**VEHICLE:** 65.4%

**ACRYLIC RESINS:** 12.4

**WATER & ADDITIVES:** 53.0

\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.

### RECOMMENDED FILM THICKNESS PER COAT:

**WET:** 5.5 mils

**DRY:** 2.0 mils

### PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS:

One gallon of Clare Primer will cover 225-275 square feet depending on the condition of your wall or surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

### AVERAGE DRY TIME @ 77°F/25°C (ASTM D 1640):

Dries to the touch in 30-60 minutes. Recommended wait time between coats is 2-4 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety).

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ; UL GREENGUARD Gold Certified

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/Safety](http://clare.com/Safety) or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead/or/asbestos](http://www.epa.gov/lead/or/asbestos), or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

Clare Primer seals and blocks out most household stains, such as crayon, pencil, ink, and felt marker. After priming stained areas, test that the stain has been sealed by applying the topcoat to a small area. More than one coat may be necessary on severe stains. Clare Primer may block minor dried water stains, however, a specialty stain-blocking primer is recommended.

Do not apply when the air or surface temperature is below 50°F.

**INGREDIENTS:** Water (07732-18-5), Acrylic Resin (25586-20-3), Talc (Asbestos-Free) (08005-37-6), Rutile Titanium Dioxide (01317-80-2), Kaolin Clay (01332-58-7), Heavy Paraffinic Petroleum Distillates (64742-65-0), Silica, Amorphous Synthetic (07631-86-9), Aluminum Hydroxide (21645-51-2), Cellulose Fiber (21645-51-2)

# Clare Exterior Siding Paint - Perfect Eggshell

## Product Information

Our Exterior Siding Paint is the ideal finish for siding and other exterior surfaces. This 100% acrylic, water-based formula is self-priming, applies easily, covers in fewer coats and is made to withstand any weather. It's premium protection from the elements, from UV rays to frost, salt, moisture, mildew, and more.

## Finish

Perfect Eggshell: A beautiful, barely there sheen ideal for siding and other exterior surfaces.

## Prep

Ensure your surface is completely clean and free of any dust, oil, mildew, wax, or other substances before painting. Power washing is recommended as the best method to thoroughly clean exterior siding. Sand or scrape any loose or peeling paint and repair any cracks, holes, or imperfections. We suggest a light sanding to dull your surface for proper adhesion. For pro-quality results, always apply two coats of paint. When painting outside, avoid extreme weather conditions. We suggest painting when the weather will be desirable and mild for several days in a row, to ensure your paint cures properly.



**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** 100% acrylic

**FINISH (ASTM D 523) EGGSHELL:** 10-15% on a 60° meter; 15-30% on an 85° meter

**COLORS:** See [www.clare.com/exteriorcolors](http://www.clare.com/exteriorcolors) for colors.

**TINT BASE:** L Tintable White, M Medium, U Ultra Deep

**VISCOSITY AT 77°F/25°C (ASTM D 562):** 100-105 KU

**MAXIMUM VOC CONTENT:** 4.5 G/L

**SOLIDS BY VOLUME (ASTM D 2697):** 38.0% ± 2%

**SOLIDS BY WEIGHT:** 49.0% ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 10.40 lbs

### COMPOSITION BY WEIGHT:

**PIGMENT:** 27.7%

**PRIME PIGMENTS\*:** 17.9

**REINFORCING PIGMENTS:** 9.8

**VEHICLE:** 72.3%

**ACRYLIC RESINS:** 19.3

**WATER & ADDITIVES:** 53.0

*\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.*

### RECOMMENDED FILM THICKNESS PER COAT:

**WET:** 3.8 mils

**DRY:** 1.5 mils

### PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS:

One gallon of Clare Exterior Siding Paint will cover approximately 350-400 square feet depending on the condition of your surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

**AVERAGE DRY TIME @ 77°F/25°C (ASTM D 1640):** Dries to the touch in 1-2 hours. Recommended wait time between coats is 4-6 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety)

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/](http://clare.com/)

Safety or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

This paint contains a preservative which inhibits the growth of mildew on the surface of the paint film.

Avoid painting excessively hot surfaces. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.

When the air temperature is at 35°F, surfaces may be colder; prior to painting. Check to ensure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid painting if rain or snow is expected within 2-3 hours, as in colder temperatures, it may require longer time before the paint film cures enough not to be affected by rain or snow.

Avoid painting on rainy days, however, Clare exterior paint will begin to resist rain after approximately 4 hours.

**INGREDIENTS:** Water (7732-18-5); Copolymer Resin (Proprietary); Titanium Dioxide (13463-67-7); Nepheline Syenite (37244-96-5); Propylene Glycol (57-55-6)

CLARE

CLARE, INC.  
246 5TH AVENUE, NEW YORK, NY 10001  
(646) 847-7746  
[WWW.CLARE.COM](http://WWW.CLARE.COM)

# Clare Exterior Trim Paint - Subtle Semi-Gloss

## Product Information

Our Exterior Trim Paint is the ideal finish for doors, trim, and other exterior surfaces. This 100% acrylic, water-based formula is self-priming, applies easily, covers in fewer coats and is made to withstand any weather. It's premium protection from the elements, from UV rays to frost, salt, moisture, mildew, and more.

## Finish

**Subtle Semi-Gloss:** A subtle, radiant sheen perfect for doors, trim, and other high-touch exterior surfaces.

## Prep

Ensure your surface is completely clean and free of any dust, oil, mildew, wax, or other substances before painting. Power washing is recommended as the best method to thoroughly clean exterior siding. Sand or scrape any loose or peeling paint and repair any cracks, holes, or imperfections. We suggest a light sanding to dull your surface for proper adhesion. For pro-quality results, always apply two coats of paint. When painting outside, avoid extreme weather conditions. We suggest painting when the weather will be desirable and mild for several days in a row, to ensure your paint cures properly.



**SOLVENT TYPE:** Waterborne

**RESIN TYPE:** 100% acrylic

**FINISH (ASTM D 523) SEMI-GLOSS:** 40-50% on a 60° meter

**COLORS:** See [www.clare.com/exteriorcolors](http://www.clare.com/exteriorcolors) for colors.

**TINT BASE:** L Tintable White, M Medium, U Ultra Deep

**VISCOSITY AT 77°F/25°C (ASTM D 562):** 85-91 KU

**MAXIMUM VOC CONTENT:** 50 G/L

**SOLIDS BY VOLUME (ASTM D 2697):** 37.0% ± 2%

**SOLIDS BY WEIGHT:** 46.5% ± 2%

**WEIGHT PER GALLON (ASTM D 1475):** 10.06 lbs

### COMPOSITION BY WEIGHT:

**PIGMENT:** 21.2%

**PRIME PIGMENTS\*:** 19.9

**REINFORCING PIGMENTS:** 1.3

**VEHICLE:** 78.8%

**ACRYLIC RESINS:** 21.7

**WATER & ADDITIVES:** 57.1

*\*Prime pigments include titanium dioxide (TiO<sub>2</sub>), plus all other pigments directly adding to the hiding power of this paint.*

### RECOMMENDED FILM THICKNESS PER COAT:

**WET:** 3.9 mils

**DRY:** 1.5 mils

### PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS:

One gallon of Clare Exterior Trim Paint will cover approximately 350-400 square feet depending on the condition of your surface.

**THINNING RECOMMENDATION:** This paint is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of paint.

**AVERAGE DRY TIME @ 77°F/25°C (ASTM D 1640):** Dries to the touch in 1-2 hours. Recommended wait time between coats is 4-6 hours. High humidity and cool temperatures may result in longer dry and recoat times.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

**PACKAGING:** One-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable.

**CLEANUP:** Clean with warm, soapy water.

**DISPOSAL:** Dispose of paint according to your local regulations, and never pour paint down your drain. For information on safe paint disposal, visit: [clare.com/safety](http://clare.com/safety)

**COMPLIES WITH:** ARB 2007 SCM & CALGreen 2013; CHPS Section 01350; SCAQMD Rule 1113; LEED® 2009 IEQ; LEED® v4 EQ

**SAFETY DATA SHEET:** Available at [www.clare.com/safety](http://www.clare.com/safety)

**SPECIAL INSTRUCTIONS:** CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. Always wear personal protective equipment while sanding and washing these surfaces. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by washing surfaces with water. For more information, visit [clare.com/](http://clare.com/)

Safety or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit [www.epa.gov/lead](http://www.epa.gov/lead) or/asbestos, or contact your state or local Health Department.

Clare paint or primer does not cause, prevent, or fix the growth of mold, mildew, or other fungi. Painted surfaces in high-moisture spaces, such as bathrooms, or homes in excessively humid climates, should have proper ventilation to help avoid mildew and mold. Excessive moisture and inadequate ventilation are typically what promotes the growth of mildew. Remedy any mold, mildew or other related issues before painting.

This paint contains a preservative which inhibits the growth of mildew on the surface of the paint film.

Avoid painting excessively hot surfaces. Do not apply at air or surface temperatures below 35°F or when air or surface temperatures may drop below 35°F within 48 hours.

When the air temperature is at 35°F, surfaces may be colder; prior to painting. Check to ensure the air, surface, and material temperature are above 35°F and at least 5°F above the dew point. Avoid painting if rain or snow is expected within 2-3 hours, as in colder temperatures, it may require longer time before the paint film cures enough not to be affected by rain or snow.

Avoid painting on rainy days, however, Clare exterior paint will begin to resist rain after approximately 4 hours.

**INGREDIENTS:** Water (7732-18-5); Copolymer Resin (Proprietary); Titanium Dioxide (13463-67-7); Nepheline Syenite (37244-96-5); Propylene Glycol (57-55-6)

CLARE

CLARE, INC.  
246 5TH AVENUE, NEW YORK, NY 10001  
(646) 847-7746  
[WWW.CLARE.COM](http://WWW.CLARE.COM)