

e-STUDIO™ 6527AC/7527AC

Introducing a new generation of Toshiba departmental MFPs – with high-performance, zero-trust security and cloud-ready features, these printers are the perfect choice for today's modern work environments.

- Highly Productive Color MFPs
- High-speed – 65 & 75 PPM Color and 75 & 85 PPM Black & White
- Leading-edge Security Features
- Cloud Print & Service Capabilities
- Built-in Optical Character Recognition



MAIN SPECIFICATIONS

Copy System	Indirect Electrostatic Photographic (ECP)/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	Color: 65/75 PPM (LT), Monochrome: 75/85 PPM (LT)
First Copy Out	Color: 6.4/5.4, Monochrome: 4.5/4.1 Seconds
Warm-Up Time	From Powering On: Approx. 20 Seconds From Sleep & Low Power: Less Than 15.4 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Four Drawer Version: Standard 2,280 Sheets/Max. 6,780 Sheets Tandem Drawer Version: Standard 3,520 Sheets/Max. 8,020 Sheets
Original Feed	300-Sheet DSDf with Double Feed Detection LD/A3
Max. Original Size	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF: 1,160 x 2 LT Only
Paper Feed Sizes	Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet External LCF LT Only Opt. 2,000-Sheet Piggyback External LCF LT Only
Paper Weights	Drawers: Standard: 540 Sheets x 4-16lb Bond-110lb Cover Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover Plus 540 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Duplex	Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Reproduction Ratio	25% to 400%
Max Duty Cycle	540K/600K Month (Color: 100%)
Weight	Approx. 470lb
Approx. Dimensions	37.6" (W) x 27.5" (D) x 48.3" (H)
CMYK Toner Yield	CMY: 39,200, K: 106,600 @ 5%
Power Source	120 Volts, 50/60 Hz, 16 Amps
Power Consumption	Maximum 2.0kW/2.4kW (120V)
Plug Type	NEMA 5-20
Memory	6GB
Hard Disk Drive	128GB Solid State Drive (SSD)

e-BRIDGE NEXT PRINT SPECIFICATIONS

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi, 1,200 x 1,200 dpi or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/Print, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite*, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPV1.0 in High Security Mode

ENERGY STAR® (V3.1), EPEAT Gold, California Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

Scan Speed	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color)
Scan Weights	9.3-110lb Bond
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-FILING SPECIFICATIONS

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

ACCESSORIES (OPTIONS)

Additional Paper Options	Software Options
Large Capacity Feeder - 2,500 Sheet	e-BRIDGE Global Print
Large Capacity Feeder - 2,000 Sheet	IPSec Enabler
LCF Connector (to Add 2K LCF)	Unicode Font Enabler
Finishing Options	Multi-Station Print Enabler
65-Sheet Staple Finisher	Per Seat License
65-Sheet Saddle-Stitch Finisher	e-BRIDGE Plus for OneDrive for Business V3.0
Hole Punch for MJ1115/MJ1116	e-BRIDGE Plus for SharePoint Online V3.0
Exit Tray	e-BRIDGE Plus for Exchange Online V3.0
Connectivity/Security Options	Workplace Productivity Bundle
FAX Unit/2 nd Line for FAX Unit	e-BRIDGE Plus for Gmail
Wireless LAN/Bluetooth	e-BRIDGE Plus for Google Workspace
Fax Over IP License Key	e-BRIDGE Plus Voice Guidance
Bluetooth Keyboard	
2 nd NIC Holder	
USB Hub	
Meta Scan Enabler	
Security SSD (512GB)	
FIPS HDD (320GB)	
Miscellaneous Options	
Card Reader Holder	
Accessory Tray	
Panel 10-Key Option	
Manual Pocket	
Harness for Coin Controller	
Accessible Arm	

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

business.toshiba.com