


Features & Benefits


- Isolated brand power supply
- Super bright LM80 LED 4014 SMD, Ra>80
- Lumen output : 100-110lm/w DLC4.3 Standard
- PF>0.9, THD≤ 15 %
- AC100-277V/AC120-347V, 0-10V dimmable
- High Quality LGP imported from Taiwan, Anti-Yellowing
- Non-flicker, no dark spot, protect your eyes
- UL cUL DLC certifications
- Ideal replacement for traditional troffer with over 80% energy saving
- 5 Years warranty

Technical Specification


Input Voltage: AC100V~277V 50Hz~60Hz / AC120-347
 THD: ≤ 15 %
 PF: >0.90 Non-Flicker
 Power Efficiency: >90 %
 LED light source: high bright SMD4014
 Color Temperature: 4000K, 5000K
 Color Rendering Index: CRI > 80
 Beam Angle: 120°
 Material: AL+High Quality LGP
 Working Temperature: -20 C ~ +45C
 Storage Temperature: -25C ~ +65C
 IP Grade : IP40
 Working Life-span: 50,000H



(1 * 4 ft)



(2 * 2 ft)



(2 * 4 ft)

LED PANEL LIGHT



Parameters

Model	Watt	Input Voltage	Lumens	LED Qty	Size	Efficiency	CCT	N.W
PL-36W-66-40-TG-12	36W	AC 100-277V 120-347V	3960(± 5%)lm	SMD4014	2 * 2 ft	100-110lm/w	4000K 5000K	3.28 kg/pc
PL-40W-123-40-TG-12	40W		4400(± 5%)lm		1 * 4 ft			3.77 kg/pc
PL-50W-126-40-TG-22	50W		5500(± 5%)lm		2 * 4 ft			6.3 kg/pc



Features & Benefits:

- 0-10V dimmable and 2.4G Wireless & CCT dimmable LED Flat Panel
- CCT adjustable from 3000K-3500K-4000K-5000K
- No need any wire connections
- UL/cUL with isolated external power supply
- LED Source: SMD2835 0.5W, CRI>80, LM80 report
- High Quality LGP, imported from Taiwan,
- Anti-Yellow
- 5 years warranty



Parameters

Model	Watt	Input Voltage	Lumens	LEDs	Size(mm)	CCT	N.W
PLR-40W-66-28-TG	40W	AC 100-277V	100-110 lm/W	SMD 2835	2 * 2 ft	3000K-5000K	3.7 kg/pc
PLR-50W-126-28-TG	50W				2 * 4 ft		7.2 kg/pc
PLR-40W-123-28-TG	40W	AC 100-277V	100-110 lm/W	SMD 2835	1 * 4 ft	3000K-5000K	5.7 kg/pc

- CCT can be adjusted between 3000K-5000K as you wish .
- Brightness Dimming: 1- Step Dimming 2- Continuous Dimming
- After 10 Seconds of each operation, it will enter the standby power saving mode.
- If you need to adjust again, please press the ON button, indicator light flashes is OK.
- A remote-controller maximum can control 4 groups of lamps , but the numbers of lamps of each group is unlimited

