



The pump is a submersible drainage pump fitted with cast iron vortex style impeller. The pump can handle particles up to 15mm.

The pump is characterised by:

- Cast iron pump body and impeller for durability
- Fully automatic operation.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Carry handle.
- Versatile outlet connection.
- 240V single phase motor with in-built thermal protection
- thermal overload.
- 10m of power cable.
- Dewatering of cellars, etc.
- Pumping clean or slightly dirty water
- Flows to 133 L/min
 - Heads to 7.0 m

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

Pump body: Cast Iron
 Impeller: Cast iron/Nylon
 Shaft: Stainless Steel
 Shaft seal: Dual mechanical seal (carbon/ceramic)

Installation:


Maximum ambient temperature: 40 °C
 Pipe connections discharge: 1.1/4" F

Electrical data:

Rated voltage: 240V
 Mains frequency: 50 Hz
 Rated output: 180W
 Current: 1.6 amps
 Capacitor: 8 uF
 Motor duty: Continuous
 Motor type: Asynchronous
 Motor protection: In-built thermal overload
 Ingress protection: IP 68
 Insulation class: B
 Power cable length: 10 m H07RNF
 Net weight: 9.3 kg

2 Year Bianco Pumpz Warranty

BULK QUANTITY APPLIES TO THIS PRODUCT





Submersible vortex drainage pump fitted with cast iron semi vortex impeller. Can pump particles up to 15mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Handy carry handle
- Hose tail adaptor included
- 240V single phase motor with built-in thermal overload protection
- 10m of power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering of cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 15mm dia.) and stringy material in suspension.
- Max Flow 150 L/min
- Max head 7.5 m

Liquid:

Liquid water temperature range: 2 – 35 °C

Materials:

Pump body: Cast Iron
 Impeller: Cast iron/Nylon
 Shaft: Stainless Steel
 Shaft seal: Dual mechanical seal - carbon/ceramic and oils seal


Installation:

Maximum ambient temperature: 40 °C
 Pipe connections discharge: 1 1/4"

Electrical data:

Rated voltage: 240V
 Mains frequency: 50 Hz
 Rated output: 250W
 Current: 1.8 amps
 Capacitor: 9 uF
 Motor duty: Continuous
 Motor type: Asynchronous
 Motor protection: Built-in thermal overload
 Ingress protection: IP 68
 Insulation class: B
 Power cable length: 10 m H07RNF
 Net weight: 10 kg

2 Year Bianco Pumpz Warranty





Submersible vortex drainage pump fitted with cast iron semi vortex impeller. Can pump particles up to 25mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch.
- Triple seal system: Dual Mechanical Seal (carbon/ceramic) and oil seal
- Handy carry handle
- Universal hose tail adaptor
- 240V single phase motor with built-in thermal overload protection
- 10m power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 25mm dia.) and stringy material in suspension.
- Pumping clean or slightly dirty water
- Max flow 200 L/min
- Max head 8.5 m

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:


Pump body:	Cast Iron
Impeller:	Cast iron
Shaft:	Stainless Steel
Shaft seal:	Dual mechanical seal - carbon/ceramic and oil seal

Installation:

Maximum ambient temperature:	40 °C
Pipe connections discharge:	2"

Electrical data:

Rated voltage:	240V
Mains frequency:	50 Hz
Rated output:	450W
Current:	3.7 amps
Capacitor:	15 uF
Motor duty:	Continuous
Motor type:	Asynchronous
Motor protection:	In-built thermal overload
Ingress protection:	IP 68
Insulation class:	B
Power cable length:	10 m H07RNF
Net weight:	19 kg



2 Year Bianco Pumpz Warranty



Submersible drainage pump fitted with cast iron semi vortex impeller.

Can pump particles up to 25mm.

Pump Characteristics:

- Cast iron pump body and impeller for durability
- Fully automatic operation by means of float switch
- Triple seal system: Dual mechanical seal - carbon/ceramic, and oil seal
- Handy carry handle
- Hose tail adaptor included
- 240V single phase motor with built-in thermal overload protection.
- 10m power cable, H07RN-F.
- For use with clean or slightly dirty water, dewatering cellars, storm-water pit emptying, dirty water with non-abrasive solids (up to 25mm dia) and stringy material in suspension.
- Max flow 300 L/min
- Max Head 10 m

Liquid:

Clean water temperature range: 2 – 35 °C

Materials:

- Pump body: Cast Iron
- Impeller: Cast iron
- Shaft: Stainless Steel
- Shaft seal: Dual mechanical seal - carbon/ceramic and oil seal

Installation:

- Maximum ambient temperature: 40 °C
- Pipe connections discharge: 2"

Electrical data:

- Rated voltage: 240V
- Mains frequency: 50 Hz
- Rated output: 750W
- Current: 5.3 amps
- Capacitor: 20 uF
- Motor duty: Continuous
- Motor type: Asynchronous
- Motor protection: Built-in thermal overload
- Ingress protection: IP 68
- Insulation class: B
- Power cable length: 10 m H07RNF
- Net weight: 21 kg

2 Year Bianco Pumpz Warranty

