

A MICRO-SPRINKLER LIKE NO OTHER

INTRODUCING THE NEW S7 SPINNER



1.0-3.4 BAR
20-285 LPH
2.4-4.9 M RAD.

FLOW CONTROL
OPTIONS & UNIQUE
QUICK-CONNECT
QUICK-CLEAN
FEATURES



NELSON IRRIGATION'S INNOVATIONS ARE TARGETED TO COMBAT RISING ENERGY AND LABOR COSTS.



- Nelson's Quick Clean (QC) technology reduces irrigator hours — simply turn, flush and reconnect.
- Flow control nozzles are flow regulating at 1 bar.
- Insect protection helps prevent plugging or stalling.
- Modular design allows quick and easy nozzle exchange.
- Optional tree starter (break off) deflector tabs offer flexibility.
- Optional PVC Stakes prevent tubing damage from vermin.

THE S7 — A MICRO-SPRINKLER WITH A NEW LEVEL OF **QUALITY, RELIABILITY AND DURABILITY**

PRELIMINARY DATA – FLOW (LPH) & RADIUS (METER)

S7 SPINNER – BLUE PLATE			PRESSURE IN BAR											
			1.0		1.5		2		2.5		3.0		3.5	
Nozzle	PN NO TAB**	PN WITH TAB**	LPH	R (m)	LPH	R (m)	LPH	R (m)	LPH	R (m)	LPH	R (m)	LPH	R (m)
*35 ORANGE	12890-2135	12890-2235	—	—	35	3.4	41	3.7	46	3.8	50	3.8	53	3.7
*40 BLUE	12890-2140	12890-2240	36	3.2	43	3.8	50	4.2	57	4.3	62	4.2	66	3.9
*45 PURPLE	12890-2145	12890-2245	46	3.5	55	4.0	65	4.3	72	4.5	79	4.4	84	4.2
*50 GREEN	12890-2150	12890-2250	57	3.8	67	4.3	77	4.4	87	4.7	95	4.6	104	4.3
*55 YELLOW	12890-2155	12890-2255	68	3.9	80	4.3	93	4.5	104	4.7	115	4.7	126	4.7
*60 LIGHT RED	12890-2160	12890-2260	80	3.9	97	4.3	113	4.6	127	4.8	138	4.9	148	4.8
*65 GRAY	12890-2165	12890-2265	103	3.9	125	4.4	145	4.7	163	5.0	179	5.0	193	5.0
*70 WHITE	12890-2170	12890-2270	122	3.9	146	4.5	169	4.8	190	5.0	209	4.9	225	4.7
*78 DARK BLUE	12890-2178	12890-2278	159	4.0	186	4.6	216	4.9	242	5.0	265	4.9	285	4.5
8.5 ORANGE 7FC*	12891-2109	12891-2209	*32	3.3	*32	3.1	*32	3.0	*32	2.9	*32	2.9	*32	3.0
11 BLUE 7FC*	12891-2111	12891-2211	*42	3.4	*42	3.5	*42	3.6	*42	3.6	*42	3.5	*42	3.3
14 PURPLE 7FC*	12891-2114	12891-2214	*53	3.8	*53	4.1	*53	4.2	*53	4.2	*53	3.9	*53	3.6
18 YELLOW 7FC*	12891-2118	12891-2218	*68	3.9	*68	4.3	*68	4.5	*68	4.4	*68	4.2	*68	3.7
24 RED 7FC*	12891-2124	12891-2224	*91	4.0	*91	4.3	*91	4.5	*91	4.5	*91	4.4	*91	4.0

*Flow through FC nozzles may vary up to 10% across the listed pressure range. Contact factory for specific flow rate information.



WARRANTY & DISCLAIMER: Nelson products are warranted for one year from date of original sale to be free of defective materials and workmanship when used within the working specifications for which the product was designed and under normal use and service. The manufacturer assumes no responsibility for installation, removal or unauthorized repair. The manufacturer's liability under this warranty is limited solely to replacement or repair of defective parts, and the manufacturer will not be liable for any crop or other consequential damages resulting from any defects in design or breach of warranty. THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSES and of all other obligations or liabilities of manufacturer. No agent, employee or representative of the manufacturer has authority to waive, alter or add to the provisions of warranty, nor to make representations or warranty not contained herein. PATENT PENDING.