

A compact valve box with 4 internal solenoid valves available in models to suit either 24 Vac or 9 Vdc latching irrigation controller. The eZyvalve™4 provides a trouble-free way to distribute water to a micro irrigation-system.

Features

- Pre-assembled with no internal pipe connections.
- High strength UV stabilised materials.
- Includes cable seal and wire connectors.
- Water, dust and pest resistant.
- Textured non-slip lid with o-ring seal and stainless steel screws.
- 3/4" threaded inlet and outlet connections.
- Easy to connect to existing garden taps using Braided Hose accessory.

Applications

Landscape, home gardens, greenhouses and nurseries. Above and below ground installation.



Performance Chart

Flow Rate (lpm)	Pressure Loss (kPa)
10	30
15	63
20	108
25	165
30	231



eZyvalve™4 - 24 Vac

Ordering Information - eZyvalve™4

Type	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
eZyvalve™4 - 24 Vac Solenoids 3/4"	16605	1	10	11.5
eZyvalve™4 - 9 Vdc Latching Solenoids 3/4"	16625	1	10	12.9



eZyvalve™4 - 9 Vdc Latching

Ordering Information - Accessories

Type	Order Code	Pack Quantity	Packs per Carton	Carton (kg)
Braided Hose 1000 mm x 3/4" BSPF	90603	1	40	16.1
Tap Adaptor 1" BSPF x 3/4" BSPM	45825	25	30	12.1



Braided Hose

Specifications

Dimensions Packaged		Connection Type	
LENGTH	105 mm	INLET OUTLET	3/4" BSPM tapered 3/4" BSPM parallel x 4
DEPTH	182 mm		
WIDTH	182 mm		
WEIGHT (approx.) - 24 Vac	1075 g		
WEIGHT (approx.) - 9 Vdc Latching	1150 g		



Operating Specifications	
FLOW RANGE	1 lpm -30 lpm
PRESSURE RANGE - 24 Vac	20 kPa - 1250 kPa
PRESSURE RANGE - 9 Vdc	20 kPa - 750 kPa
AMBIENT TEMPERATURE	2° C - 60° C
ELECTRICAL - 24 Vac	24 Vac, inrush current 320 mA, holding current 260 mA at 50 Hz
ELECTRICAL - 9 Vdc Latch	9 Vdc, inrush current 1200 mA