

SAFETY DATA SHEET

Christy's® Slick-Wrap Tape

Date Revised: APR 2015 Supersedes: MAR 2014

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Christy's® Slick-Wrap Tape

SYNONYMS:

PRODUCT USE: Repair of leaks in all types of pipes, hoses, and lines that may contain fluids, gases, or any other type of material.

SUPPLIER and MANUFACTURER T Christy Enterprises, Inc.

655 East Ball Road, Anaheim, CA 92805-5910 Tel. 1-714-507-3300 (North America) Tel. 1-714-507-3300 (International)

EMERGENCY: Transportation/Medical issues: Tel. 800.535.5053 INFOTRAC

SECTION 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Health		Environmental		Physical	Physical		
Acute Toxicity:	Category 1	Acute Toxicity:	N/A	Flammable Liquid/Aerosol/Gas:	N/A		
Skin Corrosion/Irritation:	N/A	Chronic Toxicity:	N/A				
Skin Sensitization:	N/A						
Eye:	N/A						

GHS LABEL:

Signal Word: DANGER

Hazard Statements

H317 May cause an allergic skin reaction

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

H334 May cause allergy or asthma symptoms or breathing difficulties

P272 Conatminated work clothing should not be allowed out fo the workplace.

if inhaled

P280 Wear protective gloves. P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep confortable for breathing.

Precautionary Statements

P333+P313 If skin irritation or rash occurs: get medical advice/ attention.

P342+P311 If experiencing respiratory symptoms: Get emergency medical attention.

P362+P364 Take off contaminated clothing and wash it before reuse

P501 Dispose of contents/ container in accordance w

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

	CAS#	EINECS#	REACH	CONCENTRATION		
			Pre-registration Number	% by Weight		
Polyisocyanate Prepolymer	TS			60-95		
4,4'-Diphenylmethane Diisocyanate (MDI)	101-68-8	202-966-0		5-20		
Polymeric Diphenylmethane Diisocyanate (pMDI)	9016-87-9			<15		
Diphenylmethane Diisocyanate (MdI) Mixed Isomers	26447-40-5			<5		
Polyester Resin	TS			<5		
*Zinc Sulfide	1314-98-3	215-251-3		<5		
<10% of mixture consists of ingredients of unknown acute toxicity						

Trade Secret (TS) Some items on the SDS may be designated as trade secrets. Bonafide requests for disclosure of trade secret information to medical personnel must

be made in accordance with the provisions contained in 29 CFR 19190.1200 I 1-13. The full text for all R-Phases is shown in Section 15

*This chemical is subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40CFR372).

SECTION 4 - FIRST AID MEASURES

Flush eyes immediately with plenty of water for 15 minutes and seek medical advice immediately. Contact with eyes:

Skin contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water. If irritation develops, seek medical advice. Inhalation: Remove to fresh air. If breathing is stopped, give artificial respiration. If breathing is difficult, give oxygen. Seek medical advice.

Give large quantities of water to drink. Do not induce vomiting. Seek medical advice immediately Ingestion:

SECTION 5 - FIREFIGHTING MEASURES

Suitable Extinguishing Media: 0-Minimal Dry chemical powder, carbon dioxide gas, foam **HMIS NFPA** N/A Unsuitable Extinguishing Media: Health 1-Slight Flammable Limits in Air (% by vol) Not Measured Flammability 0 0 2-Moderate **Unusual Fire and Explosion Hazards** Emits toxic fumes under fire conditions. Reactivity 0 0 3-Serious Special Firefighting Procedures 4-Severe

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal precautions: Warn other workers of spill and contain spill

Provide sufficient ventilation, use explosion-proof exhaust ventilation equipment or wear suitable respiratory protective equipment.

Wear proper protective equipment(see section 8).

Environmental Precautions: Prevent product or liquids contaminated with product from entering sewers, drains, soil or open water course. Methods for Cleaning up: disposal should be made in accordance with federal, state, and local regulations as stated in Section 13

Materials not to be used for clean up:

SECTION 7 - HANDLING AND STORAGE

Handling: Avoid breathing of vapor, avoid contact with eyes, skin and clothing. Wash hands and face after handling this material.

Wear proper protective equipment when handling this material.

Do not eat; drink or smoke while handling.

Store in ventilated room or shade below 27°C (80°F) and away from direct sunlight. Storage:

Keep out of reach of children

Follow all applicable local regulations for handling and storage.

SECTION 8 - PRECAUTIONS TO CONTROL EXPOSURE / PERSONAL PROTECTION

Always provide good general, mechanical room ventilation where this chemical/material is used.

Work/Hygiene Practices. Avoid breathing vapor. Avoid contact with eyes. Wash hands and face after handling.

Personal Protective Equipment (PPE):

Safety glasses, Chemical goggles, or face shield Eve Protection:

Skin Protection Tri-Polymer. Check with your company's glove supplier to ensure chemical resistance.

Respiratory Protection: Use a suitable respiratory protective device in case of insufficient ventilation. Follow the OSHA respirator regulations found in 29 CFR 1910.134

or the European standard EN 149. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or if irritation or other symptoms

Protective Clothing Wear suitable protective clothing to prevent skin contact.

Other Equipment Make safety shower, evewash stations, and hand washing equipment available in the work area.

FileName: Slick Wrap Page 1 of 2

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Gray, Fiberglass tape impregnated with gray liquid

Odor: Slight aromatic odor **Odor Threshold:** P.H. Not Applicable Melting/Freezing Point: **Boiling Range: Boiling Point:** 367°C (694°F) Estimated based upon components. **Evaporation Rate:**

237.8°C (460°F) Pensky-Martens Closed Cup ASTM D-93 Flash Point: Specific Gravity

Insoluble - Reacts slowly with water to liberate C02 gas

Solubility:

Partition Coefficient n-octanol/water: Not Available

Auto-ignition Temperature: N/A **Decomposition Temperature:** N/A

Approx. 5400 mPas @ 77°F (25°C) **VOC Content:**

Flammability: Flammability Limits: LEL: N/A

UEL: N/A Vapour Pressure: < 0.0001 mm Hg @ 25°C (77°F)

N/A

N/A

N/A

Vapour Density: 1.14 (Air = 1)269 Pa:s (@25°c Other Data: Viscosity:

SECTION 10 - STABILITY AND REACTIVITY

Stability: Hazardous decomposition products: None Hazardous Polymerization: Will not occur Conditions to avoid: None

Incompatible Materials: Water reacts with the chemicals in the tape.

SECTION 11 - TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:

Potential Health Effects:

Inhalation: Irritating to respiratory tract, damage to mucous membranes, allergic sensitization (Isocyanates)

Eve Contact: Eve Irritation May Result **Skin Contact:** May cause Irritation

Ingestion: No info.

Chronic (long-term) effects: None known to humans

Toxicity: LD₅₀ LC₅₀ 9016-87-9 Oral: 10 g/kg (rat) N/A

101-68-8 N/A Inhalation 4 hrs. 369 mg/m3 (rat)

1314-98-3 Oral: >15 g/kg (rat), Dermal: 2 g/kg (rabbit) N/A

Reproductive Effects Sensitization to Product Mutagenicity Synergistic Products **Teratogenicity Embryotyxicity** Not Applicable Not Applicable Poss Not Applicable Not Applicable Not Available

Only selected Registry of Toxic Effects of Chemical Substances (RTECS) data is presented here. See actual entry in RTECS for complete information.

SECTION 12 - ECOLOGICAL INFORMATION

Eco toxicity: LC50 Daphnia magna (Water flea) 970 mg/L/48 hr; static 1314-98-3

LC50 Pimephales promelas (Fathead minnow) 1826 mg/L/96 hr; static 1314-98-3

Mobility: N/A Biodegradation N/A N/A BioAccumulation:

Note: Not all of the ingredients have been tested for Eco toxicity

SECTION 13 - WASTE DISPOSAL CONSIDERATIONS

Follow local and national regulations. Water reacted product can be disposed of in municipal trash. Recommend not to dispose of rinse water containing product in a storm water drainage system. Do not reused this container. This container may be hazardous when emptied.

SECTION 14 - TRANSPORT INFORMATION

DOT, IATA, ADR, IMO/IMDG SHIPPING INFORMATION **Proper Shipping Name:** Not Regulated

Hazard Class: Identification Number:

TDG INFORMATION Packing Group:

Label Required: TDG CLASS: Not Regulated SHIPPING NAME:

UN NUMBER: Marine Pollutant: NO

SECTION 15 - REGULATORY INFORMATION

Directive 67-548-EEC Risk Phrases:

Safety Phrases:

R-20 Harmful by Inhalation Symbols: R-36/37/38 Irritating to eyes, respiratory system and skin.

R-42/43 May cause sensitization by inhalation and skin contact.

S-1/2 Keep locked up and out of reach of children

S-23 Do not breathe gas/fumes/vapour/spray S-24/25 Avoid contact with skin and eyes.

S-36/37 Wear suitable protective clothing and gloves

S-45 In case of accident or if you feel unwell seek medical advice immediately Toxic Substances Control Act (TSCA) Status: This product is in compliance with rules, regulations, and orders of TSCA.

All Components are listed on the TSCA Inventory

SECTION 16 - OTHER INFORMATION Specification Information:

Department issuing data sheet: Environmental Health & Safety All ingredients are compliant with the requirements of the European <EHSinfo@tchristv.com> Directive on RoHS (Restriction of Hazardous Substances). e-mail address:

Training necessary: Yes, training in practices and procedures contained in product literature.

Reissue date / reason for reissue: MAR 2014/ Updated GHS Information

Intended Use of Product: Repair of leaks in all types of pipes, hoses, and lines that may contain fluids, gases, or any other type of material

This product is intended for use by skilled individuals at their own risk. The information contained herein is based on data considered accurate based on current state of knowledge and experience. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof.

FileName: Slick Wrap Page 2 of 2