

LARGE FORMAT PRINTER
SURECOLOR™ SC-F6330/F7270



DESIGNED FOR PERFORMANCE,
PURPOSED FOR AFFORDABILITY.

Sleeker, faster, higher performance. Epson SureColor F-Series printers include some of the latest advancements in printing technology to deliver amazing performance at an affordable running costs. With a fresh, stylish look in black, the SC-F6330 turns any office into a modern space. The SC-F7270 is designed for roll-based production, ideal for short to medium-volume roll-to-roll custom fabric, textile and soft signage. Developed with printing technology synonymous with Epson, both the SC-F6330 and SC-F7270 uses PrecisionCore™ TFP® printhead and UltraChrome DS ink in bigger ink pack capacities for increased productivity and higher quality printing of custom clothing, soft signage, merchandise and hard surface work.



Up to
64" Wide*



1.5L Ink
Tanks



1 Year
Warranty



Environmentally
Friendly

4 COLOURS		DS EPSON ULTRACHROME DYE SUB INK	MAXIMUM MEDIA WIDTH	MAX. INK CAPACITY PER COLOUR	EPSON EDGE PRINT RIP INCLUDED	PRINT SPEEDS**			SQM/HR
						MAX SPEED	PRODUCTION	HIGH QUALITY	
	SC-F6330		44"	1.5 L		63,4	22,7	8,3	
	SC-F7270		64"			58,9	22,2	8,2	



SC-F6330
44" Wide Dye-Sub



SC-F7270
64" Wide Roll-to-Roll Dye-Sub



SC-F6330
High capacity 1.1L ink packs



SC-F7270
High capacity 1L ink packs



IT'S IN THE DETAILS.

With Epson UltraChrome™ ink, the SureColor SC-F6330/SC-F7270 delivers consistent, vibrant prints.

Remarkable Productivity

Deliver superior print quality, speed and reliability during continuous operation, with minimal downtime through Epson's advanced PrecisionCore printhead.

Affordable Prints with Peace of Mind

Cost-effective 1.1L/1L*** ink packs and new high-density black ink ensure lower ink usage and overall printing costs.

Consistent Vibrant Quality

UltraChrome DS ink is specially formulated to produce vibrant colours, intense blacks, sharp contours and smooth gradations.



Epson Edge Print

*Up to 64" wide for F7270, 44" for SC-F6330

**All speed is dependent on RIP used

***1L ink packs are for use with SC-F7270 and 1.1L ink packs are for use with SC-F6330

SPECIFICATIONS

SURECOLOR™ SC-F6330/F7270

EPSON
EXCEED YOUR VISION

Model Number	SC-F6330	SC-F7270
Printer Width	44"	64"
Printing Technology		
Print Method	PrecisionCore™ TFP® Printhead	
Nozzle Configuration	360 nozzles x 4 channels x 1 head	360 x 2 nozzles each colour (x4)
Maximum Resolution	720 x 1440 dpi	
Print Modes	Resolution	Pass
Draft	360 x 720	1
High Speed	720 x 720	2
Production	720 x 720	3
Production	720 x 720	4
High Quality	720 x 720	6
High Quality	720 x 1440	8
Print Speed (m²/h)		
	63.4	58.9
	30.4	30.3
	22.7	22.2
	15.8	16.2
	11.2	11.1
	8.3	8.2
Ink System		
Ink Type	Epson UltraChrome™ DS dye-sublimation ink	
Colours	4 colours - Cyan, Magenta, Yellow, High-Density Black	
Ink Tank Capacity	1.5L	
Ink Pack Capacity	1.1L	1L
Paper Handling		
Paper Feed Method	Rear roll feed (2" / 3" core with max 150mm diameter); Auto take-up reel support over 914.4 mm (36")	Rear roll feed (2" / 3" core with max 250mm diameter); Auto take-up reel unit
Media Width	300.0 mm (11.8") to 1117.6 mm (44")	300 to 1625.6mm
Printing Width (Margin)	Max. 1112mm Side Margin: 3mm both sides	Max. 1615.6mm Side Margin: 5mm both sides (10mm when using Media Holding Plates)
Media Thickness	Up to 1mm (over 75gsm)	0.08 - 1mm (over 75gsm)
Heat Press Condition		
Transfer Condition	Heater	
Temperature	200°C	
Time	40 sec	
Control Panel		
Colour & Size	2.7 inch colour LCD	2.5 inch colour LCD
Connectivity		
Standard	Hi-Speed USB, 100BASE-TX / 1000BASE-T	
Ethernet	10BASE-T / 100BASE-TX / 1000BASE-T	
Memory		
Main	512MB	
Network	128MB	
Printer Software		
	Communication Driver, User's Guide, EPSON LFP Remote Panel 2, EpsonNet Setup, EpsonNet Config, EpsonNet Print, EpsonEdge Print	
Electrical Specifications		
Rated Voltage	AC 100 – 240V	
Rated Frequency	50 – 60Hz	
Power Supply	1.0 - 0.5A	10 - 5A
Power Consumption		
Operating	Approx. 65W	Approx. 460W
Standby	Approx. 20W	Approx. 30W w/ heater OFF
Sleep	Approx. 3W	Approx. 10W
Power Off	Less than 0.4W	Less than 0.6W
Recommended Operating Temperature & Humidity		
	15 - 35°C; 20 - 80% RH (non-condensation)	
Bundled Items		
Ink Supply System and Waste Ink Bottle Kit	C12C932491	-
Substrate Support System and Ink Supply System	-	C12C932471
Initial Ink Pack Set	C12C934741	C12C932111
Auto Take Up Reel	C12C934671	-
Roll Adaptor	C12C934701	-
Optional		
Auto Cutter Blade	C13S902006	-
Media Holding Plate	-	C12C932121
Maintenance Kit	C13S210042	C13S210038
Waste Ink Bottle	C13T724000	C13T724000
Roll Media Adaptor	C12C811391	-

Dimensions & Weight

SC-F6330

Weight: 94kg (without ink)



Ink Pack Compatibility

1.1L Ink Packs

● High Density Black	C13T46H800
● Cyan	C13T46H200
● Magenta	C13T46H300
● Yellow	C13T46H400

SC-F7270

Weight: 274kg (without ink)



Ink Pack Compatibility

1L Ink Packs

● High Density Black	C13T741X00
● Cyan	C13T741200
● Magenta	C13T741300
● Yellow	C13T741400



©2019 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Print samples shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Dealer's Stamp

Information correct at time of printing
Printed December 2019

CAS TECHNOLOGY PTE LTD

A 10 Ubi Crescent
#05-52 Ubi Techpark (Lobby C)
Singapore 408564

T (65) 6742 8355
F (65) 6742 9897
W www.castechnology.com.sg

