

Blue - Neutral to the 'N' marking on the 'OUT' side of the control plate;

Brown - Live to the 'L' marking on the 'OUT' side of the control plate... this is **VERY** Important!

Green / Yellow - Earth... the Queensgate Thermostatic Concealed Control Panel does not require an earth wire so the 'earth' wire from the Towel Rail Element should go to the earth post in the wall box or be connected to the ring main.

The incoming 240v main Live and Neutral may now be connected. The Blue 'neutral' to the 'N' on the 'MAIN' side and the Brown 'live' to the 'L' on the 'MAIN' side. Finally, double check that the earth wire is securely connected to the earthing post on the inside of the back box together with the earth from the ring main.

Carefully fit the control plate into the back box ensuring that no wires are trapped during the fitting process and that the cable is located in the 'cut out' underneath. Use the 2 fixing screws to secure to the wall back box.

User Instructions

There are 4 buttons on the control plate. The '**ON / OFF**' button ϕ (Red), the temperature '**INCREASE / DECREASE**' buttons '<' (Blue) & '>' (Red) and the '**2HR**' boost button (Green).

Basic Operation

To turn the unit on in normal mode, press the ϕ button and release it. The red LED will light up beneath the button to show the unit is on and at least one of the five LED's below that will also become lit.

To increase or decrease the temperature, press the < > buttons to attain the desired setting. Each one of the red LED's that becomes lit signifies that 20% of the total output being used. eg if you have a 250 watt element fitted into your Towel Rail, then **1 lit red 'LED' IN THE SET OF 5**, will mean that you are using 50 watts of power, 2 led's means 100 watts etc up to full power of 5 LED's, using 250 watts.

The unit will remain on **AS LONG AS THE POWER LED REMAINS LIT.**

To turn the unit off, press the ϕ button and release it. NB The control plate contains a memory and whatever the temperature that was set when the unit was turned off, will be the temperature (number of led's lit) that the element will resume at when the unit is turned on the next time.

'2 HR' Boost' function

The boost function allows you to go to full power for a limited period of time with the press of one button. Then after a period of 2 hours, the unit will revert to the setting that was set **BEFORE** the '2HR' button was pressed. e.g. if three red LED's were lit, showing a 60% usage, and then you press the 2HR button, the green LED beneath the 2HR button will flash green for a period of two hours before going out and the power will then revert to that originally set on the red LED's.

One good feature of this function is that you can use it 'just for a 2 hour period' ie getting up in the morning etc which also means that you don't have to worry about forgetting to turn the unit off whilst you are away from your home, thus saving energy.

To operate the boost function when the unit is **SWITCHED OFF**, press the 2HR button. The red LED under the ϕ will become lit, the green LED under the 2HR button will flash green, signifying that the '2HR' function is being used and also all five red LED's will become lit to show full power is set. The unit will then switch itself off after 2 hours.