



CW3H

1800mm 3 Hole Gas Waterless Woks

CW3H-CCC 3 Hole, 3 Chimney Burners CW3H-CCD 3 Hole, 2 Chimney Burners, 1 Duckbill Burner CW3H-CDD 3 Hole, 1 Chimney Burner, 2 Duckbill Burners





Also Available





Duckbill burner



Chimney burner

1 NZ models Duckbill burner rating 105MJ/hr Natural Gas / 85MJ/hr on LP gas.

- 800mm compact depth
- Cobra suite matching
- Waterless wok deck
- 14" wok hole
- Duckbill and Chimney burner model options
- 105 MJ/hr 18 jet Duckbill burners¹
- 95 MJ/hr 24 jet Chimney burners •
- High splashback with shelf ٠
- Water folding laundry arm on splashback
- Rear waste channel
- Stainless steel spill tray •
- Lift out wok ring ٠
- Flame failure protection with pilot burner •

OVERALL CONSTRUCTION

- Full chassis construction
- Double skin insulated wok deck
- Stainless steel exterior finish
- Heavy-duty cast iron wok rings (removable)
- Stainless steel spill tray
- 63mm dia. stainless steel legs with adjustable feet

CONTROLS

- Pilot On/Off control with flame failure valve
- Main burner On/Off valve with High-Low burner adjustment
- Quarter turn main burner control handles
- Quarter turn water valve handle

CLEANING AND SERVICING

- Stainless steel exterior finish
- · Lift out wok rings for full cleaning ability
- · Slide out spill tray
- Rear waste channel with removable grate for debris collection
- · Access to all parts from front and top for servicing







СМЗН

1800mm 3 Hole Gas Waterless Woks

CW3H-CCC 3 Hole, 3 Chimney Burners CW3H-CCD 3 Hole, 2 Chimney Burners, 1 Duckbill Burner CW3H-CDD 3 Hole, 1 Chimney Burner, 2 Duckbill Burners CW3H-DDD 3 Hole, 3 Duckbill Burners





СМЗН

SPECIFICATIONS

Burners 95MJ/hr 24 jet Chimney burner 105MJ/hr 18 jet Duckbill burner (NZ - LP gas rating 85 MJ/hr) Gas Rating - Total CW3H-CCC 285 MJ/hr

CW3H-CCC 285 MJ/hr CW3H-CCD 295 MJ/hr (NZ- LP gas rating 275 MJ/hr) CW3H-CDD 305 MJ/hr (NZ- LP gas rating 265 MJ/hr) CW3H-DDD 315 MJ/hr (NZ- LP gas rating 255 MJ/hr) Wok size 14" wok ring

Suits woks 40-60cm / 16-24"

Gas connection (x3) Separate gas connection for each wok hole. R3/4 (BSP)male each wok hole 506mm from rear, 340mm from floor, 68mm, 668mm and 1268mm from RH side All units supplied with Natural-LP gas regulators for each wok connection

Supplied gas regulators include Test Point for appliance operating pressure Supplied regulator(s) must be

fitted to each appliance gas connection when installed Water connection (x2) Cold water connection

2 x 1/2" O.D. copper tube 475mm from rear, 325mm from floor, 494mm and 1094mm from RH side

Drain connection Connection to waste drain 1-1/4" BSP drain waste 107mm from rear, 647mm from floor, 203mm from LH side Dimensions Width 1800mm Depth 800mm Height 771mm Incl. splashback 1280mm Nett weight 194kg Packing data

2.19m3, 294kg Width 1835mm Depth 865mm Height 1382mm Gas types Available in Natural gas and LP gas, please specify when



ordering

an Ali Group Company

moffat.com.au moffat.co.nz

Australia moffat.com.au

Moffat Pty Limited

Victoria/Tasmania 740 Springvale Road Mulgrave, Victoria 3170 Telephone +613-9518 3888 Facsimile +613-9518 3833 vsales@moffat.com.au

New South Wales Telephone +612-8833 4111 nswsales@moffat.com.au

South Australia Telephone +613-9518 3888 vsales@moffat.com.au

Queensland Telephone +617-3630 8600 gldsales@moffat.com.au

Western Australia Telephone +618-9413 2400 wasales@moffat.com.au

New Zealand moffat.co.nz

Moffat Limited

Rolleston 45 Illinois Drive Izone Business Hub Rolleston 7675 Telephone +64 3-983 6600 Facsimile +64 3-983 6660 sales@moffat.co.nz Auckland

Telephone +64 9-574 3150 sales@moffat.co.nz





Standard

All Cobra products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd AN.C.01.19 / 1598

