



Blast chiller 20 X 1/1 GN pan capacity - DO20

Quick Overview

- Digital controller with probe and temperature display
- Stainless Steel interior and exterior
- Internal rounded corners for easy cleaning
- Insulation in 60mm thickness CFC free polyurethane
- Adjustable Stainless Steel feet
- Self-closing door with magnetic gasket
- Ambient operation temperature 43 ° C and 65% RH

Description

Blast Chiller- DO20

- ADVANCED DESIGN
- ALL STAINLESS STEEL
- Ambient operating temp. 43°C
- Blast Chilling Performance +3°C
- Blast Freezing Performance -18°C
- Digital controller with probe and temperature display
- Stainless Steel interior and exterior
- Internal rounded corners for easy cleaning
- Insulation in 60mm thickness CFC free polyurethane
- Adjustable Stainless Steel feet
- Self-closing door with magnetic gasket
- Ambient operation temperature 43 ° C and 65% RH
- 415V; 2.25kW; 3 phase unit
- Process 70 kg from 90 ° C to -18 ° C in 180 mins
- Stainless steel interior and exterior, with the exception of the external base in galvanised steel
- Rounded internal corners
- Insulation thickness: 40 mm
- Self-closing door with hinges on the left and magnetic gasket
- Chamber probe.
- Core probe.
- Universal stainless steel pan grids
- Space between grids 65mm
- Internal volume: 340L

Dimension

- 750mmW x 740D x 2090/2120H

2 Years Parts and Labour Warranty

Your Shipping Specifications

Packing Width (mm)	770
Packing Depth (mm)	780
Packing Height (mm)	2190
Power	415V; 3 phase
Warranty	2 Years Parts and Labour