

# Panda TB

H 205 • 225

P 85

L 125 2p • 188 3p

**3L1** frozen food & ice-cream

	TN	TB	TB/TN	TC	TC/TN	N
	Chiller	Freezer	Dual Temp	Heated	Hot&Cold	Non-refrigerated
RS - Static						
RV - Ventilated		•				
RS/TC S - Static and Dry Heat convertible						
RV/TC S - Ventilated / Dry Heat convertible						
HUR - Meat						
CH - Chocolate						
TC S - Dry Heat						
TC BM - Bainmarie						
N - Non-refrigerated						

## Installation

- Plug-in air-cooled
- Plug-in water-cooled

## Temperature range

-23 / -25 °C

## Refrigerant

R290

## Refrigeration

Ventilated

## Defrost

Hot Gas

## Climate Class

3L1

## Illumination

- LED lighting on canopy
- Vertical LED lighting

## Side panels

- Panoramic with safety glass
- Blind

## Shelves

5 grid shelves

## Closing system

Triple pane glass doors

## Base

4 adjustable feet

## Available colours

Colori disponibili

• Standard / Di serie

□ On request

### Inside

□  RAL

### Outside

•  RAL

### Side panels

•  RAL



## Panda TB

		125 2p	188 3p
External dimensions (LxDxH) including side panels	85	1350 x 850 x 2100 mm	1980 x 850 x 2100 mm
	85 HT	1350 x 850 x 2300 mm	1980 x 850 x 2300 mm
Capacity (gross/net)	85	1308 / 955 lt	1962 / 1432 lt
	85 HT	1490 / 1088 lt	2236 / 1632 lt
Net weight	85	471 kg	707 kg
	85 HT	508 kg	762 kg
Refrigeration		Ventilated	
Refrigerant		R290	
Climate class		3L1	
Operating conditions		25 °C / 60 %RH	
Product temperature		-18/ -16 °C	
Compressor (type)		1 Hermetic	2 Hermetics
Defrost		Hot Gas	
Power supply		230 V / 1 Ph / 50 Hz	

Dimensions include side panels: both panoramic and blind side panels are 50 mm thick

Height Altezza	Length Lunghezza	Model type Tipo di banco	Total display area m <sup>2</sup>	Temperature class	Recommended temperature °C	Energy class	Energy efficiency index EEI	Annual energy consumption kWh/A	Light source type and class
H205	125 2P	IVF2	2,75	L1	-20°C	D	38,87	9.459	-
	188 3P	IVF2	3,56	L1	-20°C	D	42,02	12.864	-
H225	125 2P	IVF2	3,14	L1	-20°C	D	36,40	9.957	-
	188 3P	IVF2	4,06	L1	-20°C	D	39,27	13.542	-

Configuration: air-cooled plug-in unit R290, vertical LED lighting, non-illuminated shelves, panoramic end side panels

