

UD505DAUS10

Family	Dishwasher
Subfamily	Undercounter Dishwasher
Basket dimensions	500x500 mm
Panel	Ecoline 2016
Filter	4-stages filter system
Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	340 mm
Power connection	230 V~ / 10 A / 2,2 kW /50 Hz
Depth with open door	1000 mm
Product dimensions WxDxH	578x600x814 mm



Distribution

Solutions	Hotels; Restaurants/Catering; QSR
-----------	--------------------------------------

Aesthetics

Serie	Ecoline	Led color	Red
Control panel	Electronic		

Functions



Functionality	GN 1/1 trays washing; 4-stages filter; HTR; Door clearance 340mm
---------------	--

Programs

Programs	3 automatic programs; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program specifications	Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank 60°C-2'30"; Boiler 85°C/Tank 60°C-4'
Drain and self cleaning cycle	Yes
Maximum basket/hour	40
Maximum dishes/hour	720

Interface

Display	4 digit	On/Off button	Yes
Number of buttons	5	Manual diagnostic	Yes

Construction

Tank Construction	With printed base Single wall	Rack guides	Embossed
Tank material	Stainless steel AISI 304	Tank capacity	16 l
Back panel	Galvanized	Boiler capacity	6 l
Door	Double wall	Rumorosità	Lpa 55,5 dBA
Tank filter	Plastic	Protection class	IPX4
Washing spray arm	Stainless steel	Adjustable feet	Yes
Rinse spray arm	Plastic	Net weight	53,000 kg
Door gasket	Only up	Drain max. height	600 mm

Technical Features

Tank heating element	1500 W	Water inlet	8°C
Boiler heating element	1500 W	Max temperature inlet water	60°C
Washing pump	680 W	Max water hardness	12°F - 7°dH
Default connection	1200 W	Water inlet	Cold 15°C
Water cycle consumption	3,2 l		

Electrical Connection

Plug	Australian 10 AMP
------	-------------------

Equipments

Drain pump	Yes	Cycle counter	Yes
Peristaltic detergent doser	Yes, electronic control	Break tank	Yes
Peristaltic rinse-aid doser	Yes, electronic control	Partial renewal of water in the tank and built-in drain pump	Si
Default chemicals dosing unit of measure	gr/l	Trays washing option GN1/1 530x325mm	Yes
Boiler thermostop	Yes default ON	Water supply pipe diameter	16 mm
Soft Start	Yes	Drain supply pipe diameter	21,5 mm
Automatic start	Yes, default OFF	Peristaltic detergent doser	Yes, manual
Detergent load	Yes, manual	Peristaltic detergent doser	Yes, manual
Rinse load	Yes, manual		

Accessories Included

Dish basket	PB50D01	Water supply pipe	In acciaio Watermark
Cutlery basket	PHOOS02	Drain pipe	Yes - 2m
Flat basket	1x PB50G02		

Not included accessories

WB50PG5

Wire basket for no. 25 plastic glasses with flat bottom, 500x500x260 mm




WH00S01

Wire insert for 12 small dishes

PB50D01

Basket made of polypropylene for 18 plates 500x500



WS5

Underframe for glasswashers 500mm



PHOOS01

Single basket in polypropylene for cutlery



PHOOS02

Basket in polypropylene for cutlery with 6 compartments



Symbols glossary (TT)



...



...



5 stand filter



MAX.USABLE HEIGHT 340mm