

# UD511MDAUS

Family	Dishwasher
Subfamily	Undercounter Dishwasher
Basket dimensions	500x500 mm
Panel	Ecoline 2016
Filter	5-stages filter system
Rinse pump H.T.R. system	Rinse pump with atmospheric boiler
Usable load height	400 mm
Power connection	230 V~ / 13 A / 3,0 kW / 50 Hz
Depth with open door	1020 mm
Product dimensions WxDxH	600x600x822 mm



## Distribution

Solutions	Hotels; Restaurants/Catering; QSR
-----------	--------------------------------------

## Aesthetics

Serie	Easyline	Led color	Green
Control panel	Electronic		

## Functions



Functionality	GN 1/1 trays washing; 5-stage filter; HTR; Door clearance 400mm
---------------	---

## Programs

Programs	6 automatic programs; 1 fully programmable program; Self-cleaning programs
Program options	Extra rinse; Clean water cycle
Program specifications	Boiler 85°C/Tank 60°C-60"; Boiler 71°C/Tank 60°C-1'20"; Boiler 85°C/Tank 60°C-1'10"; Boiler 85°C/Tank 60°C-1'30"; Boiler 85°C/Tank 60°C-3'; Boiler 71°C/Tank 60°C-2'10"; Boiler 85°C/Tank 60°C-4'10"
Drain and self cleaning cycle	Yes
Maximum basket/hour	51

Maximum dishes/hour 918

## Interface

Display	4 digit	Cycle progress alert	Yes
Number of buttons	5	End-cycle alert	Yes
On/Off button	Yes	Manual diagnostic	Yes

## Construction

Tank Construction	Deep drawn Double wall	Door gasket	On 3 sides
Tank material	Stainless steel AISI 304	Rack guides	Embossed
Back panel	Galvanized	Tank capacity	11 l
Door	Double wall	Boiler capacity	6 l
Balanced door	Yes	Rumorosità	Lpa 56,5 dBA
Tank filter	Stainless steel	Protection class	IPX4
Washing spray arm	Stainless steel	Adjustable feet	Yes
Rinse spray arm	Stainless steel	Net weight	56,000 kg
		Drain max. height	600 mm

## Technical Features

Tank heating element	2000 W	Water inlet	8°C
Boiler heating element	2300 W	Max temperature inlet water	60°C
Washing pump	700 W	Max water hardness	12°f - 7°dH
Default connection	3000 W	Water inlet	Cold 15°C
Water cycle consumption	3,2 l		

## Equipments

Drain pump	Yes	Rinse load	Yes, manual
Peristaltic detergent doser	Yes, electronic control	Break tank	Yes
Peristaltic rinse-aid doser	Yes, electronic control	Partial renewal of water in the tank and built-in drain pump	Si
Chemicals level probe	Yes, optional KITSONLIV	Trays washing option GN1/1 530x325mm	Yes
Default chemicals dosing unit of measure	gr/lit	Water supply pipe diameter	16 mm
Boiler thermostat	Yes default ON	Drain supply pipe diameter	21,5 mm
Stand-by system	Yes	Peristaltic detergent doser	Yes, manual
Automatic start	Yes, default OFF	Peristaltic detergent doser	Yes, manual
Detergent load	Yes, manual		

## Accessories Included

---

<b>Dish basket</b>	PB50D01	<b>Water supply pipe</b>	Yes - 2m
<b>Cutlery basket</b>	PHOOS02	<b>Drain pipe</b>	Yes - 2m
<b>Flat basket</b>	1x PB50G02		

## Not included accessories

### WB50PG5

Wire basket for no. 25 plastic glasses with flat bottom, 500x500x260 mm



### KITSONLIV

Probe level kit



### PHOGR5

Glass basket for 500x500 mm glasswashers




### WH00S01

Wire insert for 12 small dishes



### PHOOS01

Single basket in polypropylene for cutlery



### PB50G02

Universal basket in polypropylene 500x500




### WB50T02

Wire basket for 5 trays 600x500



### WB50G01

Universal wire basket with flat bottom 500x500



### PB50D01

Basket made of polypylene for 18 plates 500x500



### WB50G02

Wire basket for glasses with inclined bottom 500x500



### KITDETKCC500

Kit for detergent (1l) and rinse storage (1l) for dishwashers 500x500



### WB50G04

Wire basket for glasses with inclined bottom 500x500



### PHOOS02

Basket in polypropylene for cutlery with 6 compartments



### WB50G03

Wire basket for glasses with inclined bottom 500x500



### WS5

Underframe for glasswashers 500mm

## Symbols glossary (TT)

---



...



...



Max usable height 400mm



5 STAGE FILTER