



**Remark:**

- 100% Open/Short Test
- Conductive Resistance: 5ohms MAX
- Insulation Resistance: 10M ohm MIN.
- HI-POT: DC 300V/10MS.
- The product is Reach/RoHS 2.0 compliant.
- Support 1080P/3D/4K\*2K@60Hz.

Item NO.	Length(m)
HDMI-75FTMM-C	22.86m(75ft)
HDMI-100FTMM-C	30.5m(100ft)

DESCRIPTIONS & SPECIFICATIONS	QTY	REMARK
HDMI Protective Cap, PE	2PCS	
Heat-shrink tube	Heat-shrink tube, "Screen >>>>"	1PC
Heat-shrink tube	Heat-shrink tube, "Source >>>>"	1PC
	Chipset	1PC
External Mold	Outer Mould 45P PVC, Black	2PCS
Innernal Mold	Inner Mould PE	2PCS
Connector	HDMI A PLUG PIN, Gold-Plated	2PCS
Cable	26AWG 2.0V (19+1BC) 128ALB HDMI Cable OD: 8.5mm [(1/0.404BC+FPE)*1P+D+AL] *5C + (1/0.404BC+HDPE)*4C + AL + D + 128ALB + PVCOD8.5mm CL3 PVC	2PCS

TOLERANCES UNLESS OTHERWISE STATED

X = ±1  
.X = ±0.2  
.XX = ±0.1

AYAGROUP			
ERP NO.:		SAMPLE DWG NO.:	
DOC No.:		REVISION	A0
CUSTOMER:		UNIT	mm
CUSTOMER P/N:		SCALE	NO
DESCRIPTION	HDMI 2.0V 26AWG 19+1	PAGE NO	1/1
		DATE	2018/09/
APPROVAL	CHECKED	DRAWN	