

Servicing Guide

Just like your car, regular service extends the life of your Oscar M stroller.

Below are some helpful tips to keep your wheels smooth and enjoyable to use. We recommend servicing your stroller at least every 6 months and an inspection at least once a month.

HERE'S HOW TO SERVICE YOUR OSCAR M AT HOME:

- **WARNING:** Do not immerse or rinse your stroller in water.
- **Inspect all the rivets and screws** that connect your stroller together. They should be clean, tight and secure.
- **Remove the wheels** (back and front) and wipe them clean with a clean rag to remove any dirt, sand or other debris. Wipe out the wheel housing. Rear wheels only: Spray the wheel pins with some WD-40 to keep the wheel release running smoothly.
- **Make sure the fold joints are free of dirt and debris.** Wipe clean with a damp cloth. We suggest cleaning the fold joints when the stroller frame is folded. Apply some WD-40 or Silicone spray (available at Bunnings, Mitre 10 or your local supermarket) to the moving hinges.
- **To prevent the metal components from rusting,** wipe down your stroller frame with a damp clean rag after beach or rain use, especially when used in windy and exposed areas. Always store in a dry place. Do not store your stroller in a damp environment that is not well insulated (such as an unfinished basement or outdoor shed).
- **If you live or use the stroller within 2kms of the beach or sea,** every 2 months liberally spray a rag with some WD-40 and wipe it over the rivets and screws to add an additional coating layer against corrosion. **FINE SAND CAN INTERFERE WITH THE BRAKES: AVOID WHERE POSSIBLE.**
- **If you do find some corrosion forming on the rivets or screws,** you can wipe it clean with a damp cloth. Dry it overnight, then liberally apply a layer of WD-40 as above. Repeat monthly.

If you have any questions relating to servicing your stroller, email us hello@edwardsandcobaby.com or call New Zealand: 09 869 8950 Australia: 02 90666702

Washing instructions

FRAME WASHING INSTRUCTIONS

Clean with a damp rag and a little mild detergent (such as dishwashing liquid or car wash detergent). Dry thoroughly. DO NOT use abrasives (such as "Jif") because they may scratch your stroller frame.

FABRIC WASHING INSTRUCTIONS

For Stroller Shoulder Pad, Carry Cot Cover, Carry Cot Liner, Carry Cot Mattress Cover, Capsule Shoulder Pad, Capsule Canopy

Machine wash (front loader only) in cold water, gentle cycle with mild detergent. Dry flat and away from direct sunlight. Do not dry clean, iron or bleach.



COLD GENTLE
CYCLE



DRY FLAT



DRY IN SHADE



DO NOT
DRYCLEAN



DO NOT
IRON



DO NOT
BLEACH

For Capsule Seat Cover, Capsule Newborn Insert

Spot clean or hand wash in cold water with mild detergent. Dry flat and away from direct sunlight before re-use or storage. Do not dry clean, iron or bleach.



HAND WASH



DRY FLAT



DRY IN SHADE



DO NOT
DRYCLEAN



DO NOT
IRON



DO NOT
BLEACH

For Stroller Seat Cover, Stroller Canopy

Spot clean with a damp cloth. Do not wet excessively. Do not dry clean, iron or bleach.



DO NOT
DRYCLEAN



DO NOT
IRON



DO NOT
BLEACH