INSTALLATION INSTRUCTIONS FOR MAGNETIC LICENCE PLATE FRAME

Thank you for choosing to purchase our product. Please take the time to fully read over these instructions before attempting your install. This will greatly speed up the installation process and minimize any difficulties you may encounter.

Kit includes:

- 1 License plate frame
- 2 High strength rubber coated magnets
- 4 Screw cap covers
- 4 Flat head screws
- 4 Nuts
- **Step 1:** Ensure that your licence plate is clean and fit it to the included licence plate frame. The backside of the frame has 2 tabs to hold the plate in place. Once assembled these tabs should be visible from the backside and positioned on the bottom
- **Step 2:** Position the magnets on the backside of the plate/frame assembly, lining up the holes, and ensuring that the rubber side is facing outwards. Also ensure that the magnets do not stick out past the border of the plate frame.
- **Step 3:** Place one of the included flat head screws in each plate hole and fit a nut to each screw on the backside. If you choose to use the screw cap covers use one per hole and fit them at this time between the head of the screw and the face of the plate frame.
- TIP: Start each screw and nut until all 4 are in position before tightening them down.
- Step 4: Tighten down all 4 screws. If screw cap covers are fitted snap their lids in place
- **Step 5:** Using a straight edge (credit card works fine) confirm that neither the nut or the tip of the screw sticks out beyond the surface of the magnet. **This is VERY IMPORTANT or you could scratch your paint.**
- **Step 6:** With the assembly built, choose the location you want to stick your plate to and let the magnets do the rest!

LABOUR ESTIMATE GUIDE

5 minutes