

Carbine Radius

Rack & Pinion Door Closer
 Slide arm pack for CDC-3 incl screws
 Instructions
 CDC-3

14 John Hines Ave
 Minchinbury NSW 2770
 www.carbine.com.au

Baber Lock & Key New Zealand
 16 Parkhead Pl Albany 0632 NZ
 www.baberlocknkey.co.nz



1

1. Prepare fixing holes in door and frame (use template)
 2. Assemble arm to body at 22.5° to back face.
 Secure arm and rail foot with bolts provided.

2

3. Fix body to door (4 screws).
 Slip rail foot into track and insert end cap.

3

4. Push track and arm towards frame and secure in position (2 screws).

4

NO.1 CLOSING
 NO.2 LATCHING

See instructions on rear of trim plate

5. When adjusting please note there is a MAXIMUM OF 2 TURNS. Over adjustment will affect the performance of the closer. In such instance our Guarantee becomes VOID.

5

6. Insert trim plate and lower spindle cover.

Regular Fixing - Pull Side

54, 52.4, 48, 66.5, min. 40

Max. Opening 180°

FIT ARM MECHANISM(22.5°)

R.H, L.H

Transom Fixing - Push Side

52.4, 64, 70, 12, max. 50, 43, 48

Max. Opening 180°

FIT ARM MECHANISM(22.5°)

R.H, L.H