

# Carbine Radius

Rack & Pinion Door Closer  
 Slide arm pack for CDC-5 incl screws  
 Instructions  
 CDC-5

14 John Hines Ave  
 Minchinbury NSW 2770  
 www.carbine.com.au

Baber Lock & Key New Zealand  
 16 Parkhead Pl Albany 0632 NZ  
 www.baberlocknkey.co.nz



**1**

1.Prepare fixing holes in door and frame (use template)  
 2.Assemble arm to body at 45° to back face. Secure arm and rail foot with bolts provided.

**2**

3.Fix body to door (4 screws).  
 Slip rail foot into track and insert end cap.

**3**

4.Push track and arm towards frame and secure in position (2 screws).

**4**

See instructions on rear of trim plate

NO.2 Latching  
 NO.1 Closing  
 Back Check  
 Adjusting the force SW5

5.When adjusting please note there is a **MAXIMUM OF 2TURNS**.Over adjustment will affect the performance of the closer.In such instance our Guarantee becomes VOID.

**5**

6.Insert trim plate and lower spindle cover.

### Regular Fixing-Pull Side

40  
 524  
 46  
 min. 40

FIT ARM MECHANISM (45°)

R.H L.H

Max. Opening 180°

### Transom Fixing-Push Side

524  
 60  
 31  
 min. 75  
 max. 50  
 45  
 46

FIT ARM MECHANISM (45°)

R.H L.H

Max. Opening 120°