



Material Safety Data Sheet

Issue Date: February 25, 2010 Revised Date: April 15, 2019

Reason: S1 Added Importer details S15 Added Australian Regulation Information

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Super Lube® Dri-Film Aerosol Item No: 11006, 11016

Product use: Lubricant

Importer / Supplier Company address:Contact Information:Locksmith Supply Company Pty LtdTelephone: 03 9329 7222

140-158 Dryburgh Street Emergency telephone: 03 9329 7222 & Poisons 13 11 26

North Melbourne, VIC 3051 Internet: www.lsc.com.au

Emergency Phone Number: 13 11 26 (Poisons Information Centre)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Physical state: Aerosol WHMIS hazard class: A, B.5

Color: Translucent HMIS RATING:

Odor: Aliphatic Health: 1

Fire: 4 Physical: 0

DANGER:

CONTENTS UNDER PRESSURE VAPOR MAY CAUSE FLASH FIRE

HARMFUL IF INHALED

CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Vapors and mists will irritate the respiratory tracts and

nasal passages. Overexposure may cause nervous system depression. Extreme overexposure may result in

F+ EXTREMELY FLAMMABLE

unconsciousness and possibly death.

Skin contact: Irritating to skin.

Eye contact: Contact with eyes will cause irritation.

Ingestion: Not expected under normal conditions of use.

Existing conditions aggravated

by exposure:

None generally recognized.

See Section 11 for additional toxicological information.

Classification of the substance or mixture

- Hazardous Chemical as listed on HCIS
- Dangerous Goods listed on ADG Code 2017 Table 3.2.3

GHS Label Elements:



GHS02 (Flame)



GHS07 (Exclamation Mark)



GHS08 (Health Hazard)



GHS09 (Environment)



GHS02 (Flame)



GHS04 (Gas Cylinder)

Chemical	Code	Health Hazard Statement	Hazard Category	Signal Word
Hexane 110-54-3	H315 (Causes skin irritation) H361f (Suspected of damaging fertility) H336 (May cause drowsiness or dizziness) H373 (May cause damage to organs through prolonged or repeated exposure) H304 (May be fatal if swallowed and enters airways) H225 (Highly flammable liquid and vapour)		Skin irritation – category 2	Warning
			Reproductive toxicity – category 2	
			Specific target organ toxicity (single exposure) – category 3	
			Specific target organ toxicity (repeated exposure) – category 2	
			Aspiration hazard – category 1	
			Flammable liquid – category 2	
H411 (Toxic to aquatic life with long-lasting effects)		Hazardous to the aquatic environment (chronic) – category 2		
Butane 106-97-8	H220 (Extremely flamma	ble gas)	Flammable gas – category 1 Gasses under pressure	Danger
Polytetrafluoroeth				
ylene 9002-84-0				
Carbon Dioxide 124-38-9				

Precautionary Statements - Prevention				
P264	Wash thoroughly after handling			
P280	Wear protective gloves			
P201	Obtain special instructions before use			
1201	Obtain special instructions before use			
P202	Do not handle until all safety precautions have been read and			
	understood			
P281	Use personal protective equipment as required			
P261	Avoid breathing dust/fume/gas/mist/ vapours/spray			
	3 , , , , , , , , , , ,			
P271	Use only outdoors or in a well-ventilated area			
P260	Do not breathe dust/fume/gas/mist/ vapours/spray			
P210	Keep away from heat/sparks/open flames/hot			
	surfaces. – No smoking			
	<u> </u>			
P233	Keep container tightly closed			
P240	Ground/Bond container and receiving equipment			
P241	Use explosion-proof electrical/ventilating/ lighting//equipment			
P242	Use only non-sparking tools			
P243	Take precautionary measures against static discharge			
P280	Wear protective gloves/eye protection/face protection			
P273	Avoid release to the environment			
Precautionary Statements - Response				
P302 + P352	IF ON SKIN: Wash with plenty of soap and water			
P321	Specific treatment (see on this label)			
	Reference to supplemental first aid instruction			
P332 + P313	If skin irritation occurs: Get medical advice/attention			
P362	Take off contaminated clothing and wash before reuse			
P308 + P313	IF exposed or concerned: Get medical advice/attention			
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a			
	position comfortable for breathing			
P312	Call a POISON CENTER or doctor/physician if you feel unwell.			
P314	Get medical advice/attention if you feel unwell			
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician			
P331	Do NOT induce vomiting			
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all			
1303 11301 11333	contaminated clothing. Rinse skin with water/shower			
P370 + P378	In case of fire: Use for extinction			
P391	Collect spillage.			
Precautionary Statements – Storage				
P405	Store locked up			
P403 + P235	Store in a well-ventilated place. Keep container tightly closed			
P405	Store locked up.			
Precautionary Statements – Disposal				
P501	Dispose of contents/container to			
	in accordance with local/regional/national/international			
	regulations			

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	<u>%</u>	ACGIH TLV	OSHA PEL	OTHER
Hexane 110-54-3	27-32	50 ppm TLV	176 mg/m³ TWA	None
\times_{Xn} , F , F , N ;R11-38	3-48/20-0	62-65-67-51/53		
Propane	27-32	1000 ppm TWA	$1800 mg/m^3$	None
74-98-6 F+; R12				
Butane	27-32	1000 ppm TWA	2400mg/ m^3	None
106-97-8 F+; R12				

Additional information: For the wording of the listed risk phrases refer to section 16.

Other components

Polytetrafluoroethylene 9002-84-0	3-5	Not established	Not established	None
Carbon Dioxide 124-38-9	1-3	5000 ppm TWA	9100mg/ m ³	None
Proprietary Additives	1-2	Not established	Not established	None

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. Restore breathing.

Skin contact: After contact with skin, wash immediately with plenty of

water. Immediately flush skin with plenty of water (using soap, if available). Get medical attention if

symptoms develop and persist.

Eye contact: Rinse immediately with plenty of water, also under the

eyelids, for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Get medical attention

immediately.

Notes to physician: Treatment:

5. FIRE-FIGHTING MEASURES

Flash point: Not available

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: 1.1 (vol %)

Flammable/Explosive limits-upper %: 9.5 (vol %)

Extinguishing media: Carbon dioxide (CO2). Dry chemical. Foam.

Special fire fighting procedures: Water spray may be ineffective. Water should be used

to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to

extreme heat.

Unusual fire or explosion hazards: Closed containers may rupture (due to build up of

pressure) when exposed to temperatures exceeding

120°F (48.9°C).

Hazardous combustion products: Oxides of carbon.

Sensitivity to mechanical impact: Not available

Sensitivity to static discharge: Not available

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: No information available

Clean-up methods: Remove all ignition sources. Ventilate area. Soak up

with inert absorbent.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Avoid contact with

eyes, skin and clothing. Do not breathe mist or vapors.

Storage: Do not puncture, incinerate, or expose to temperatures

above 48.9° C (120° F). Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause

containers to burst.

Incompatible products: None reasonably foreseeable.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls: Local exhaust ventilation is recommended when general

ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: If personal exposure cannot be controlled below

applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH.

Skin protection: Chemical resistant, impermeable gloves.

Eye/face protection: Safety glasses with side-shields.

See Section 3 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Aerosol
Color: Translucent
Odor: Aliphatic
Odor Threshold: Not available

Vapor pressure: $5.0 - 5.5 \text{ BAR} @ 20^{\circ} \text{ C}$

pH: Not applicable
Boiling point/range: Not available
Melting point/range: Not available
Specific gravity: Not available
Vapor density: Heavier than air
Evaporation rate: Faster than ether
Solubility in water: Not soluble
Partition coefficient (n-octano/water): Not available

VOC content: 99.2%

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous polymerization: Will not occur.

Hazardous decomposition products: None under normal use.

Incompatibility: None known.

Conditions to avoid: Heat, flames and sparks.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Not available

Toxicologically synergistic products: Not available

Refer to the following for irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Ingredient Toxicity Data & Carcinogen Status

Hazardous components	LD50s & LC50s	Other LD50s and LC50s	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	ACGIH- Carcinogen
Hexane 110-54-3	Inhalation LC50 (Rat) = 620 g/m ³	Oral Rat, LD50,25gm/kg	No	No	No	No
Propane 74-98-6	Inhalation LC50 (Rat) = 800000 ppm/15 min.		No	No	No	No
Butane 109-97-8	Inhalation LC50 (Rat) = 658 g/m ³ /4hrs		No	No	No	No
Other components						
Polytetra- fluoroethylene 9002-84-0	Not determined	None	No	No	No	No
Carbon Dioxide 124-38-9	Inhalation LC50 Human = 100000 ppm/min.	None	No	No	No	No
Proprietary Additives	Not determined	None	No	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Hexane 110-54-3	Central nervous system, respiratory system, eyes,
	skin, peripheral nervous system, testes.
Propane 74-98-6	Central nervous system
Butane 109-97-8	Central nervous system
Other components	
Polytetrafluoroethylene 9002-84-0	Irritant
Carbon Dioxide 124-38-9	Harmful by inhalation
Proprietary Additives	Not determined

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with federal and local

regulations.

14. TRANSPORT INFORMATION

Transportation of Dangerous Goods – Ground:

Proper shipping name: Consumer Commodity, ORM-D

Hazardous class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA):

Proper shipping name: Aerosols, Flammable

Hazardous class or division: 2.1 Identification number: UN 1950 Packing group: Y203

Exceptions: (Not more than 500 ml) May qualify as Consumer

Commodity ID8000

Water Transportation (IMO/IMDG):

Proper shipping name: Aerosols, LTD. QTY.

Hazardous class or division: 2

Identification number:UN 1950Packing group:NoneMarine pollutant:None

15. REGULATORY INFORMATION

15.1 Safety, health and environment regulations/legislation specific for the substance or mixture

Regulatory	Chemical	Status
Australian Inventory of	Hexane 110-54-3	Listed
chemical substances (AICS)	Butane 106-97-8	Listed
(NICNAS)	Polytetrafluoroethylene 9002-84-0	Listed
	Carbon Dioxide 124-38-9	
		Listed
Australian Hazardous	Hexane 110-54-3	Listed
Substances Information	Butane 106-97-8	Listed
System List (HCIS)		
Australian Exposure	Hexane 110-54-3	Listed
Standards (HCIS, SWA)	Butane 106-97-8	Listed
	Carbon Dioxide 124-38-9	Listed
International Agency for	Polytetrafluoroethylene9002-84-0	Listed
Research on Cancer (IARC)		
Monographs		
Poisons Schedule		

Code letter and hazard designation of product:

F+ Extremely flammable.

Risk phrases:

- 12 Extremely flammable.
- 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapors may cause drowsiness and dizziness.

Safety phrases:

- 3/7 Keep container tightly closed in a cool place.
- 16 Keep away from sources of ignition-No smoking.
- 23 Do not breathe fumes/aerosol.
- 51 Use only in well ventilated areas.

Special labeling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use.

Keep out of reach of children.

National regulations:

Water hazard class:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Page **9** of **7**

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing

on the Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on

the Toxic Substances Control Act Inventory.

SECTION 16: OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Product Regulations.

Relevant R-phrases:

12 Extremely flammable

38 Irritating to skin.

51/53 Toxic to aquatic organisims, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapors may cause drowsiness and dizziness.

Data prepared by Environment protection department.