

SPECIFICATION



FEATURES

- Support 8ch 1080P unreal-time encoding;
- Support XVi,AHD, TVI,CVI, CVBS, IP video input;
- support VGA maximum 1080P output, HDMI up to 1080P output;
- Mini 1U Case, 1SATA(Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL,3G, WIFI, IP search, Alarm center, etc ;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit,unique triple watchdog function
- Support WEB, CMS, VMS, MYEYE Platform;
- Support coaxial control

DIMENTION



System	
Main processor	Hi3521D
Video	
Video compression	H.265
Encode	8*4M-N@18fps(6 in 1); 8*1080P@18fps(6 in 1)
Decode	4*4M-N@18fps(6 in 1); 4*1080P@18fps(6 in 1)
preview	8*4M-N (6 in 1) 8*1080P (6 in 1)
Playback	4ch
Multi mode input	Analog:8*1080P;8*1080N
	Hybird:4*1080P (analog)+4*1080P (network)
	IP: 8*1080P+8*960P;4*3M;4*5M
Audio	
Audio compression	G.711A
Intercom	Support
Management	
Record mode	Manual>Alarm>Motion detection>Timing
Inquire mode	Inquire by Time/Calendar/Event/Channel
Storage mode	HDD Storage, Network Storage
Backup	Network, USB, SATA
Interface	
Video input	8*BNC (Support Coaxitron)
HDMI output	1*HDMI (MAX:1080P)
VGA output	1*VGA (MAX:1080P)
Audio I/O	1/1
Alarm I/O	0/0
Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
PTZ control	1*RS485, Support for multiple PTZ protocol
USB Port	2*USB2.0 ports
HDD	1*SATA interface (Up to 8TB)
General	
Temperature	0 °C - + 55 °C
Humidity	10% -90% RH
Power supply	12V/2A
Consumption	<10W (Without HDD)
Weight	Around1KG
Dimension	255mm(L)* 236mm(W)* 44mm(H)

