



FEATURES

- 2MP high-definition pixels, ultra low illumination;
- Infrared 10 meters infrared night vision, two-way voice;
- PTZ 355 degree horizontal, and 70 degree vertical;
- Support motion detection, APP alarm push;
- Support Auto tracking;
- Support 128G TF card storage and cloud storage;
- Power supply: DC5V 1A (Included)

SPECIFICATION

Camera	
Product name	2MP PTZ Camera
Operation mode	WATASHI IoT
Main chip	RTS3903
Sensor	F37
Resolution ratio	HD: 1920×1080; SD: 720P(1280*720)
Lens	3.6mm
Infrared night vision	Maximum support 10 meters, through the automatic photosensitive resistance control infrared open
Full color night vision	Non-support
Switch mode	Automatic
Main Function	
Pan & Tilt PTZ	horizontal 355 degrees, Vertical 70 degrees
Audio input	Support, G.711A
Two way intercom	Support
ONVIF	Non-support
Wi-Fi transmission	Support, IEEE 802.11b/g/n
RJ45 network interface	Non-support
Motion detection	Support
Automatic tracking	Support
Alarm push	Support
Remote viewing / playback	Support
Cloud storage	Support
Local storage	Max support 128G TF card
Other Parameters	
Light sensitivity	0.02lux
Image coding and decoding	H.264
Video system	1080P@20FPS, 720P@20FPS
Video mode	HD/SD
Picture flip	Support
Working stream	Main stream1.2~1.5Mbps, Sub stream512Kbps
Sound alarm	Non-support
Weak binding	Support
Network transmission	Support 2.4GHz wireless network; support WPA and WPA2 encryption
Power Supply	DC5V 1A
Power waste	<5W
Working temperature	-10°C~ 55°C
Working humidity	10% ~ 80% no condensation
Appearance size	70*110.9 (mm)
Weight	312g

