



FEATURES

- 8-CH 1080P/960P/720P Live View & 4-CH Synchronous Playback @1080P/960P/720P
- Easy configuration, plug & play and auto setup functionality.
- Auto search & add IP Cameras in the same LAN for local display & recording
- Add serial for IP Camera in other areas by use Camera WATASHI Model WIP052, WIP058, WIP087, WIP089, WIP148S, WIP149S
- Compatible with ONVIF protocol
- 1080P HDMI Local Video Output
- Auto Adaptive Stream for Efficient Display
- PTZ Support
- Monitored by Smart Phone / CMS /IE Browser supported

DIMENTION



SPECIFICATION

System	
CPU	HI3520D
OS	Embedded Linux
Storage	
HDD Device	Internal tray*1
HDD Max. Capacity	4 TB
Video	
Video Input	8CH* 1080P/960P/720P
Decoding Capacity	H.264, NTSC@30fps, PAL@25fps
Video Output	VGA*1@1080P, HDMI*1@1080P
Live View Display	8 Channel Multi Layout display: 1x1,2x2,2x3,3x3
PTZ Control	Panel Control
PTZ Operation	Direction Control, Home, Iris, Preset, Cruise
Snapshot	JPEG
Privacy	Supported (the connected camera should be with this function)
Motion Detection	Supported (the connected camera should be with this function)
Audio	
Audio Format	G.711U
Two Way Talk	No
Audio Input	Through Network
Audio Output	HDMI Output
Record/Playback	
Recording Mode	Continuous, Schedule, Manual, Event
Record Video Format	AVI/H.264 Raw/H.264 PRV
Playback Display	1CH or 4CH playback Simultaneously
Playback Control	Play, Pause, Rewind, Next / Previous Frame, Speed Control
Search Mode	Calendar, Event, Timebar
Network	
Protocols	TUTK, Onvif, P6S(private)
Interface	1 x 10/100/1000Mbps
Remote Viewing	
Smart Phone	iPhone/Android supported
PC	IE Browser/CMS
External I/O	
Video Output	VGA*1, HDMI*1
Alarm In/Out	No
Audio In/Out	No
RS485	No
USB	USB 2.0*2
General	
Power	DC12V 2A
Power Consumption	≤15W (without hard disk)
Dimension	260x220x40mm(LxWxH)
Net Weight	730g(Without hard disk)
Working Temp	-10°C ~ +50°C 10% ~ 95%RH

