



FEATURES

- Compatible with HDCVI/HDTVI/AHD
- Transmission signal: 720P/1080P
- Cable: CAT 5/5e/6
- No power required
- Transmission Distance HDCVI 720P : 400m / 1080P : 250m , HDTVI 720P/1080P : 250m , AHD 720P : 350m / 1080P : 200m

DIMENTION

Typical Application



SPECIFICATION

Properties	
Transmission Signal	1 channel
Transmission Distance	HDCVI 720P : 400m / 1080P : 250m HDTVI 720P/1080P : 250m AHD 720P : 350m / 1080P : 200m
Category Type	UTP CAT5/5E/6
Video Transmission Propertion and Port	
Coaxiai Video connector	BNC-M
Twisted-pair Video connector	Push-terminal
Compatible Format	HDCVI/HDTVI/AHD
Resolution	720P/1080P
Anti-interference	>60db
Protection	
ESD	Ia contact discharge electricity level 3
	Ib air discharge electricity level 3
	Per: IEC61000-4-2
Coaxial cable connector	2KV(common-code) Per: IEC1000-4-5
UTP Cable Connector	2KV(different-code), 4KV(common-code), Per: IEC1000-4-5
Impedance	
BNC male	75 ohms
UTP cable	100 ohms
Physical Properties	
Dimension (L*W*H)	36.5mm*17.5mm*17.3mm
Shell	ABS
Color	Black
N. W.	22.6g
Stability	
MTBF	>10000H
Environmental	
Operating Temperature	-10-55°C
Storage Temperature	-20-70°C
Humidity	0-95% (non-condensing)

