



product description

HYBRI-SIL[®] is an adhesive/sealant based on MS Polymer chemistry. The product is odorless, neutral and isocyanate free. The low VOC formula meets American and European safety and environmental regulations regarding the emission of volatile organic compounds (VOCs).

basic uses

HYBRI-SIL[®] can be used to seal windows, doors, column joints, gutters, vents and ducts, roofs, crown molding and trim, siding and most areas where a sealant is needed.

HYBRI-SIL[®] as an adhesive has a superior bond to most substrates, including porous and non-porous surfaces.

features

- Low VOC formula
- Can be applied from 0°F to 140°F
- Waterproof
- Can be applied to dry, damp or wet surfaces
- No water washout
- No odor
- Paintable with latex based paints
- Does not shrink, crack or peel
- Quick cure

packaging

HYBRI-SIL[®] is available in 9 fl oz. (266 ml) plastic cartridges with detachable 4" nozzle.

storage

Product shelf life is 12 months for unopened cartridges stored between 40°F to 80°F.

colors

White, Black, Bronze*

limitations

- Not recommended for application on Teflon, polypropylene or polyethylene surfaces.
- Not for use on underwater application or for expansion joints.
- Some alkyd paints may not be compatible with HYBRI-SIL[®].

typical properties

Application Temperature: 0°F to 140°F

Shrinkage: 0%

Skimming Time: 15 minutes

Cure Time: 24/48 hours

Hardness Shore A: 40

Temperature Resistance after Cure: -75°F to 350°F

Paintability: Acrylic or Latex paints

Cleanup: Mineral Spirits

Shelf Life: 12 months

Storage Temperature: 40°F to 80°F

paintable

HYBRI-SIL[®] is paintable with almost all common acrylic-based paints. Test alkyd-based paints for suitability. HYBRI-SIL[®] can be painted after 1 hour of cure under normal atmospheric conditions.

availability

Immediately available from Siroflex distributors strategically located throughout the U.S.

cost

Cost information is available from your local Siroflex distributor or by calling our customer service department at 1-800-359-6398.

NOTICE TO PURCHASER: Siroflex warrants its products to conform to Siroflex published specifications. The user shall determine the suitability of the product to their particular application. THE FOREGOING WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THOSE OF THE MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN. Manufacturer's and seller's liability for damage hereunder shall not exceed the purchase value of the goods used. IN NO EVENT SHALL MANUFACTURER OR SELLER BE RESPONSIBLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING OUT OF OR IN CONNECTION WITH THE USE OF THIS PRODUCT BY BUYER, BUYER'S USER, OR ANY OTHER PERSON. Notification of claim must be sent in writing to Siroflex, Inc. The notice should contain a statement as to how the product failed to meet our warranty, the proof of purchase and the amount of refund claimed.

* Please contact Siroflex customer service for additional color availability.