

KEC-2117 User Guide

Classic Electric Kettle

Capacity

INTRODUCTION

Thank you for purchasing KEC-2117 . Please read and follow the instructions thank you for purchasing to ensure your product operates correctly.

Thank you for purchasing to ensure your product operates correctly. Thank you for purchasing KEC-2117 . Please read and follow the inf in this manual carefully to ensure your product operates correctly. Efficient & rapid boiling Food grade SUS304 stainless steel body and interior Food grade SUS304 stainles Fasy arin erannomic handle Fasy arin erannomic handle

- Concealed heating elements: dry hall grafection

  Rear water level indicator

  Cordless 360° power base with cord winder for easy storage Efficient & rapid boiling General Features Easy grip ergonomic handle Cordless 360° power base with cord winder for ea Cordless 360° power base with cord winder for ea Concealed heating elements; dry boil protection Concealed heating elements; 2500-3000W Capacity: 1.7L; Power: 2500-3000W
  - Easy grip ergonomic nanor

Fill the kettle with water ( Do not exceed the "MAX" line ).

Close and push the lid ase to the power of automatically ( [ ON/OFF ] switch returns to " O" ).

Close and power Source, and considering the lid ase to the power of automatically ( [ ON/OFF ] switch returns to " O" ).

Connect the ON/OFF ] switch downward to " of automatically ( [ ON/OFF ] switch returns to " O" ). **Boiling**1. Lift the kettle, pull off the lid.

2. Fill the kettle with water ( Do not exceed the " MAX " line ).

2. Fill the kettle with the lid downward to make sure it is locked to make sure it is locked. HOW TO OPERATE

Stop Boiling

1. Push [ ON/OFF] switch upward to " O " to cut power off when boiling.

Do not switch the kettle on with insufficient or no water inside.

To not switch the kettle on with insufficient or no water inside.

The Dry Boil Protection function will automatically shut power off water. You can use it again now.

The Dry Boil Protection function will automatically it with cold water to spill out, resulting in the protection function with a base and fill it with cold water to spill out, resulting may cause hot water to spill out, resulting may cause hot water to spill out, resulting may cause hot water to spill out of the kettle form its base and fill it water from source when not using the kettle.

The Dry Boil Protection, lift the MAX indication.

The Dry Boil Protection, lift the kettle form the MAX indication.

The Dry Boil Protection function with a maintain of the power Plug or maintain of the power Plug or Power Cord is damaged, or if the Power Plug or Power Plug or Power Cord is damaged, or if the Power Plug or Do not switch the kettle on with insufficient of no water inside.
The Dry Roil Protection function will automatically education function. SAFETY PRECAUTIONS

- into the electrical outlet.

  The spilling out.

  The cause short circuit, electric shock or malfunction.

  ause short circuit, electric shock or malfunction.

  cause short circuit, electric short circuit, electric shock or malfunction.

  cause short circuit, electric short circuit, electric short ci
- Water Level Indicator ON / OFF Switch ( / O )
- 2. and Power Indicator
- Power Base

Spout

- 4. Handle



