KEC-2317 User Guide

Classic Electric Kettle

Capacity

INTRODUCTION

Thank you for purchasing KEC-2317. Please read and follow the instructions of the content of the Thank you for purchasing KEC-2317. Please read and follow the in in this manual carefully to ensure your product operates correctly. Efficient & rapid boiling Food grade SUS304 stainless steel body and interior Food grade SUS304 stainles Fasy arin erannomic handle Fasy arin erannomic handle

- Rear water level indicator Cordless 360° power base with cord winder for easy storage Cordless 360° power base with cord windertion Efficient & rapid boiling General Features Easy grip ergonomic handle Cordless 360° power base with cord winder for ea Cordless 360° power base with cord winder for ea Concealed heating elements; dry boil protection Concealed heating elements; 2500-3000W Capacity: 1.7L; Power: 2500-3000W
 - Easy grip ergonomic nanor

Boiling1. Lift the kettle, pull off the lid.
2. Fill the kettle with water (Do not exceed the "MAX" line):
3. Close and power Base to the power source, kettle starts boiling, sand the returns to "O").
3. Close and power Base to the power source, and place kettle with water (Base to the power source).
4. Connect the Power Base to the starts boiling, switch returns to "O").
5. Push the [ONIOFF] switch downward to "O".
6. When boiling completes, power is turned off. HOW TO OPERATE

Stop Boiling1. Push [ON/OFF] switch upward to " O " to cut power off when boiling.

Do not switch the kettle on with insufficient or no water inside.

To not switch the kettle on with insufficient or no water inside.

The Dry Boil Protection function will automatically shut power off water. You can use it again now.

The Dry Boil Protection function will automatically it with cold water to spill out, resulting in protection function with a passe and fill it with cold water to spill out, resulting may cause hot water to spill out, resulting may cause hot water to spill out, resulting may cause hot water to spill out of the kettle form its base and fill iman and the kettle.

The Dry Boil Protection, lift the kettle form its base and fill it water from source when not using the kettle.

To not fill the kettle electric shock or malfunction.

Disconnect the year of the power plug or power Cord is damaged, or if the Power Plug is loosely insured that water from soilling out.

Disconnect the kettle if the Power plug or Power Source water from soilling out.

Disconnect the kettle if the Power plug or Power Source water from soilling out.

Close the Lid securely to prevent hot water from soilling out. Do not switch the kettle on with insufficient or no water inside.
The Dry Roil Protection function will automatically education function will automatically education. SAFETY PRECAUTIONS

- into the electrical outlet.

 The spilling out.

 The
- cause short circuit, electric shock or malfunction.

 ause short circuit, electric shock or malfunction.

 cause short circuit, electric short circuit, electric shock or malfunction.

 cause short circuit, electric shock or malfunction.

 cause sho
- Water Level Indicator ON / OFF Switch (/ O) 2.
- and Power Indicator 3 Power Base
- 4. Handle
- Lid
- Spout



