

# gabriel ash

## the upright coldframe - specification

Dimensions – 754 x 1260 x 1390mm high

For further information call 01829 271 888

or visit [www.gabrielash.com](http://www.gabrielash.com)

### **Cedar**

The framework and cladding is in a top grade Western Red Cedar which is grown on the Western Sea Board of North America.

It has long been used in inclement climates in the construction and garden industries due to its longevity (the timber contains natural preservatives), stability (it doesn't warp or bend being straight grained) and strength. All of cedar is sourced from certified or sustainable forests.

Cedar absorbs moisture readily which brings the natural preservatives to the surface, it does however give off absorbed moisture rapidly in its natural state which causes no harm and is a natural process. There is a wide colour variation in the raw material, it mellows to a silver grey as exposed to weathering.

### **Glass**

All our structures are glazed in Toughened Safety glass to British Standard BS.6206

### **Fixings**

These are a combination of solid brass and stainless steel, both being suitable for use with Western Red Cedar due to their resistance to corrosion by the timber itself and extreme weather conditions.



### **Aluminium**

We use Powder coated Aluminium to provide improved weather protection.

The cedar lid is protected on the exterior by capping's with neoprene gaskets securing the glass and ensuring weatherproofing.

All our coldframes have an aluminium plinth that raises the timber off the ground protecting from rising moisture and preventing the cedar from being in direct contact with the ground.