



### ● FEATURES

- CO<sub>2</sub>, humidity and temperature measurement
- Dual wavelength NDIR CO<sub>2</sub> sensor (Non-Dispersive Infrared) for superior stability.
- User operated CO<sub>2</sub> calibration
- Data Hold & Max/Min/STEL/TWA function
- Adjustable auto power off timer
- Internal CO<sub>2</sub> alarm buzzer
- Backlight display function
- Datalogging up to 32,000 sets
- USB interface ,PC software included

### ● SPECIFICATIONS

<b>Measurement Range:</b> CO <sub>2</sub> : 0 ~ 30000 ppm Temperature: 0 to 50°C (32 to 122°F) Humidity: 0 ~ 100%RH
<b>Accuracy:</b> CO <sub>2</sub> : ± (75 ppm + 3% of reading) (0 ~ 5000 ppm) Temperature: ± 1.0°C Humidity: ± 4.5%RH
<b>Resolution:</b> 1 ppm, 0.1°C/0.1°F, 0.1%RH
<b>Response Time:</b> 20 seconds
<b>Battery Type:</b> 9V alkaline battery
<b>Battery life:</b> Approximately 10 hours normal use (alkaline battery)
<b>Operating Condition:</b> 0°C to 50°C(< 90%RH)
<b>Storage Condition:</b> -20°C to 60°C(< 75%RH)
<b>Dimensions:</b> 226.5 x 65 x 38.5 mm
<b>Weight:</b> 273 g
<b>Accessories:</b> 9V Battery · Instruction Manual · micro USB cable · Windows software · Carrying case.

★ **NEW!**



LED Back Light



**CENTER**<sup>®</sup>  
**CENTER TECHNOLOGY CORP.**

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,  
 New Taipei City 238, Taiwan  
 TEL: 886-2-26763926 E-Mail: center@centertek.com  
 FAX: 886-2-26763925 http: //www.centertek.com

\* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: