

FEATURES



- CO₂, humidity and temperature sensors.
- Dual wavelength NDIR CO₂ sensor (Non-Dispersive Infrared) for superior stability.
- User operated CO₂ calibration.
- Data Hold & Max/Min/STEL/TWA function.
- Adjustable auto power off timer.
- Internal CO₂ alarm buzzer.
- Datalogging up to 32,000 sets.
- USB interface, PC software included.
- Backlight display function.

SPECIFICATIONS

| |
|--|
| Measurement Range: CO ₂ : 0 ~ 30000 ppm (5000~30000 ppm over range) Temperature: -20 to 60°C (-4°F to 140°F) Humidity: 0 ~ 100%RH |
| Accuracy: CO ₂ : ± (75 ppm + 3% of reading) (0 ~ 5000 ppm) Temperature: ± 0.8°C Humidity: ± 3%RH |
| Resolution: 1 ppm, 0.1°C/0.1°F, 0.1%RH |
| Response Time: 20 seconds |
| Power Source: 9V alkaline battery or Micro USB |
| Battery life: Approximately 10 hours normal use (alkaline battery) |
| Operating Condition: 0°C to 50°C (< 90%RH) |
| Storage Condition: -20°C to 60°C (< 75%RH) |
| Dimensions: 284.5 x 65 x 38.5 mm |
| Weight: 304 g |
| Accessories: 9V Battery · Instruction Manual · micro USB cable · Windows software · Carrying case. |

★ **NEW!**



LED Back Light



Certificate No. 49Q13377

CENTER®

CENTER TECHNOLOGY CORP.

4F, No.415, Jung-Jeng Road, Shu-Lin Dist.,
New Taipei City 238, Taiwan
TEL: 886-2-26763926 E-Mail: center@centertek.com
FAX: 886-2-26763925 http: //www.centertek.com

* The specifications and other information in this catalogue are subject to change without prior notice.

Distributed by: