


Product Specifications

FlashCheck Jumbo Display Auto-Cal Needle Probe Thermometer

Measurement Range	-40°F to 311°F (-40°C to 155°C)
Operating Range	32°F to 122°F (0°C to 50°C)
Accuracy	±1°F (14°F to 194°F), ±0.5°C (-10°C to 90°C) or ±1% whichever is greatest
Response Time	Less than 6 seconds between 32°F to 77°F (0°C to 25°C)
Sensor	Thermistor
Display Resolution	0.1°F/°C
Display Reading Update	Every 2 seconds
Display Window Size	1.5 in W x 0.5 in H (38mm W x 12.7mm H)
Calibration	Automatic Calibration button
Battery	Button cell alkaline
Body Casing	ABS Plastic
Probe Length	3.9 in (99mm)
Probe Diameter	0.14 in (3.56 mm), 14 gauge needle tip 0.067 in (1.7mm)
Waterproof Rating	IP56
Factory Calibration	NIST traceable calibration
Compliance Certificate	Manufacturer's Certificate of Compliance, NIST traceable, CE, RoHS



Model 11063

- °F/°C selectable
- Automatic calibration feature
- Needle tip ideal for measuring temperature of thin mass foods such as meat patties, chicken and fish fillets, per FDA Food Code 4-302.12 (B)
- Small diameter probe provides less than 6 second response time
- Highly visible dual scale jumbo LCD display
- Sealed unibody construction
- IP56 waterproof, sanitizable, dirt and grease resistant
- Automatic shut off saves battery

DeltaTrak manufactures products under an ISO 9001:2008 registered quality management system

Patent No.
5,709,476
5,801,968



SS 11063 18B2

