

# SPHERE I

4W | 220 lm | 2000-2800K

SPHR-G50-4W-2000/2800K-E26-MP-120V

Sphere Small 4W WoD 2000K to 2800K E26 Matte Porcelain US LED Bulb


Tala's Sphere I light bulb is a refined and effective light source. Boasting Dim to Warm and flicker-free behaviour, Sphere I can dim from a cool, bright light, to its lowest setting while maintaining a warm, amber glow. Fitted with an E26 base cap, this is a stylish solution for any number of table, floor or ceiling lights.

tala®




## PHYSICAL

Bulb diameter:	2in
Bulb length:	3 1/5in
Glass shape:	G16
Base:	E26
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	23g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— CIE180  
— CIE120

IES/LDT photometry files and product photography available on request



## ELECTRICAL

Power:	4W
Current:	0.04A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	55 lm/W
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2000-2800K
Lumens:	220 lm
Incandescent equiv.:	22W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	101
TM30 - Rf	94



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 40 g	Gross weight: 0.32 kg
L 2 1/6 x W 2 1/6 x H 3 1/7 in	L 25 x W 4 1/4 x H 2 4/9 in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

## EAN

5060400152919

# SPHERE I

4W | 220 lm | 2000-2800K

SPHR-G50-4W-2000-2800K-E12-MP-120V

Sphere Small 4W WoD 2000K to 2800K E12 Matte Porcelain US LED Bulb


tala®

Tala's Sphere I light bulb is a refined and effective light source. Boasting Dim to Warm and flicker-free behaviour, Sphere I can dim from a cool, bright light, to its lowest setting while maintaining a warm, amber glow. Fitted with an E12 base cap, this is a stylish solution for any number of table, floor or ceiling lights.




## PHYSICAL

Bulb diameter:	2in
Bulb length:	3 2/8in
Glass shape:	G16
Base:	E12
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	18g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— CIE180  
— CIE120

IES/LDT photometry files  
and product photography  
available on request



## ELECTRICAL

Power:	4W
Current:	0.04A
Voltage:	110-120V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	55 lm/W
Lifetime:	15,000 hrs

## ILLUMINATION

CCT:	2000-2800K
Lumens:	220 lm
Incandescent equiv.:	22W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	101
TM30 - Rf	94



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 30	Gross weight: 0.32
L 2 1/8 x W 2 1/8 x H 3 1/8in	L 25 x W 4 2/8 x H 2 4/8in

us.tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

## WARRANTY

2 years

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights

## EAN

5060400152896