# **LED T8 TUBE LIGHT**



# **HPTB01 Series**













### Model

TB01-22W-27VDDK

Note: "27V" represents 120-277VAC

## Certifications

- DLC 5.1 Premium
- ETL





## **Description**

Adjustable LED tube light with 10W-22W wattage and CCT options (3500K-6500K). Durable aluminum housing, 120° beam angle, and >80 CRI. DLC 5.1 Premium & ETL certified, 50,000-hour lifespan, and 5-year warranty. Perfect for various applications.

#### Construction

- Durable aluminum housing and plastic lens.
- Compatible with most instant- and programmed-start electronic T8 ballasts
- · Selectable CCT and wattage.

#### **Flectrical**

- Five adjustable Wattage: 22/18/15/12/10W
- 120-277VAC input voltage
- Power factor >0.9, THD <20%</li>

### **Optics**

- 5CCT adjustable: 3500K,4000K,5000K,5700K,6500K
- CRI: >80
- 120° beam angle

# Weight

22W(Unit) 0.51lb

#### Mount

Type A+B(Single-end or Double-end Wiring)

## **Application**

- Offices
- Garage
- Stores
- Schools

#### Lifespan

• Estimated 50,000-hour LED lifespan


### Warranty

5-year warranty





# **Dimension**



TB01-22W

# **Features & Specifications**

Model	TB01-22W
Operating Voltaga	120 - 277V AC
Power	10/12/15/18/22W
Power Factor	>0.9
Current	0.18A@120V 0.08A@277V
Lumens	Max.3050lm
Efficacy	125lm/W
Color Temperature	3500K/4000K/5000K/5700K/6500K
CRI	>80
Ballast Compatibility	Type A+B
Beam Angle	120°
Certification	ETL,DLC
Life Span	50,000 hours
Operating Temperature	4°F to 113°F(-20°C to 45°C)
Material	Plastic+Aluminum
Color Finish	White
Warranty	5 Years