

Item#: 91019
LED 360° DIRECT WIRE DOWNLIGHT
FOUR PIN-BASE REPLACEMENT LAMP FOR CFL

FEATURES

- Elegant and modern appearance
- No Ballast Required
- Consume up to 80% less energy, and are environmentally friendly

APPLICATION

Replacement for CFL PL lamps with a G24q 4 pin base.

ELECTRICAL

ELECTRICAL			
Wattage	12W		
Voltage	100-277V		
Power Factor	0.9		
Total Harmonic Distortion (THD)	19		
LIGHTING PERFORMANCE			
Lumens	1320		
Lumens Per Watt (LPW)	110		
Color Temperature (CCT)	5000K		
Color Rendering (CRI)	80		
Beam Angle	360°		
Light Distribution	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1		
Dimmable Lighting Control	COUT COMMANDAL CO		
ENVIRONMENT			
Operating Temperature	-4° ~ 113°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP65		
Suitable Fixture Type	Enclosed		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Epistar - SMD2835		
CONSTRUCTION			
Housing	Aluminum / PC		
Base / Power Supply	G24q / 4 Pin		
Finish	White		

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: 91019 LED 360° DIRECT WIRE DOWNLIGHT

DIMENSIONS (Inches)

Length (MOL)	6.2"
Width/Diameter (MOD)	1.8"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		
IES Download from Web Item	VIEW		
Photometric	VIEW		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50	10811768028765	14.6" x 10.2" x 10.6"	19
Individual Box	1	811768028768	6.5" x 1.8" x 1.8"	0.4
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
91019	LED 12WT10/50K/360°/FR/100-277V/G24Q 4 PIN	N/A	50

ADDITIONAL INFORMATION:

Family Item(s): 71019/3500K - 81019/4000K