

Item#: 42019 LED 360° DIRECT WIRE DOWNLIGHT

MEDIUM BASE REPLACEMENT LAMP FOR CFL

FEATURES

- Elegant and modern appearance
- No Ballast Required
- Consume up to 80% less energy, and are environmentally friendly

APPLICATION

Replacement for CFL PL lamps with a medium base.

ELECTRICAL

Voltage100-277VPower Factor0.9Total Harmonic Distortion (THD)19LIGHTING PERFORMANCELumens1320Lumens Per Watt (LPW)110Color Temperature (CCT)5000KColor Rendering (CRI)80Beam Angle360°Light DistributionType VSBUG Rating (Backlight, Uplight, and Glare)B1 - U3 - G1Dimmable Lighting Control🔊
Total Harmonic Distortion (THD) 19 LIGHTING PERFORMANCE 1320 Lumens 1320 Lumens Per Watt (LPW) 110 Color Temperature (CCT) 5000K Color Rendering (CRI) 80 Beam Angle 360° Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Control
LIGHTING PERFORMANCE Lumens 1320 Lumens Per Watt (LPW) 110 Color Temperature (CCT) 5000K Color Rendering (CRI) 80 Beam Angle 360° Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Control
Lumens1320Lumens Per Watt (LPW)110Color Temperature (CCT)5000KColor Rendering (CRI)80Beam Angle360°Light DistributionType VSBUG Rating (Backlight, Uplight, and Glare)B1 - U3 - G1Dimmable Lighting ControlImage: ControlENVIRONMENTImage: Control
Lumens Per Watt (LPW) 110 Color Temperature (CCT) 5000K Color Rendering (CRI) 80 Beam Angle 360° Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Second Se
Color Temperature (CCT) 5000K Color Rendering (CRI) 80 Beam Angle 360° Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Control
Color Rendering (CRI)80Beam Angle360°Light DistributionType VSBUG Rating (Backlight, Uplight, and Glare)B1 - U3 - G1Dimmable Lighting ControlImage: ControlENVIRONMENT
Beam Angle 360° Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Control
Light Distribution Type VS BUG Rating (Backlight, Uplight, and Glare) B1 - U3 - G1 Dimmable Lighting Control Image: Control
BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control
Dimmable Lighting Control
ENVIRONMENT
Operating Temperature -4° ~ 113°F
Suitable Location DAMP
Ingress Protection Rating IP65
Suitable Fixture Type Enclosed
LIFESPAN
Average Life (Hours) 50,000
Warranty (Years) 5
COMPONENTS
LED Light Source Epistar - SMD2835
CONSTRUCTION
Housing Aluminum / PC
Base / Power Supply E26 - Medium
Finish White

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **42019** LED 360° DIRECT WIRE DOWNLIGHT

DIMENSIONS (Inches)

Length (MOL)	6.5″
Width/Diameter (MOD)	1.8″
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		
IES Download from Web Item	VIEW		
Photometric	VIEW		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50	10811768028796	14.6" x 10.2" x 10.6"	19
Individual Box	1	811768028799	6.5" x 1.8" x 1.8"	0.4
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
42019	LED 12WT10/50K/360°/FR/100-277V/MED	No	50

ADDITIONAL INFORMATION:

Family Item(s): 22019/3500K - 32019/4000K