

Item#: 19638
LED MINI WALL PACK

OUTDOOR NON-CUTOFF AND SEMI-CUTOFF WALL-MOUNTED AREA LUMINAIRES

FEATURES

- · Easy installation
- Replaces 50W HID
- Sealed housing for outdoor applications
- Polycarbonate optical lens
- With Photo Cell

APPLICATION

Ideal for security, pathway and perimeter lighting, building entry ways and walkways.

ELECTRICAL

LLLUTINOAL			
Wattage	23W		
Voltage	120-277V		
Current	0.23A		
Power Factor	0.9		
Total Harmonic Distortion (THD)	13.2		
LIGHTING PERFORMANCE			
Lumens	3174		
Lumens Per Watt (LPW)	136		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	73		
R9 (Red Value)	-34		
R13 (Skin Tones)			
Beam Angle	90°		
Light Distribution	Type IV, Very Short		
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G2		
Dimmable Lighting Control	("Dimmable 0-10V, Range 10% - 100%		
ENVIRONMENT			
Operating Temperature	-22° ~ 113°F		
Suitable Location	WET		
Ingress Protection Rating	IP65		
LIFESPAN			
Average Life (Hours)	50,000		
Warranty (Years)	5		
COMPONENTS			
LED Light Source	Luxeon 3030 2D		
Driver	WP-HLA-030U		
CONSTRUCTION			
Housing	Aluminum Alloy / PC		
Lens	Clear		
Base / Power Supply	Hard Wired		
Finish	Black		





QUALIFICATIONSModel Number

Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


MWP-25-[D,P]-40K

Item#: 19638 LED MINI WALL PACK

DIMENSIONS (Inches)

Length	8.3"
Width	5.5"
Height	3.5"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		
IES Download from Web Item	VIEW		
LM79	VIEW		
LM80	VIEW		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	8	10811768022978	16.5" x 12.6" x 8.7"	16.3
Individual Box	1	811768022971	5.6" x 3.9" x 8.5"	2
Country of Origin	China			
HS Tariff	9405.11.8020			

ORDERING Qualification Model # MWP-25-[D,P]-40K

ITEM#	DESCRIPTION	CASE
83691	LED MINI WALL PACK/25W/40K/CL/DIMM/120-277V/BLK/PHOTO CELL - DLC °	8
REPLACEMENT PARTS		
WP-HLA-030U	REPLACEMENT DRIVER FOR MINI WALL PACK	1

ADDITIONAL INFORMATION:

Family Item(s): 83689 without Photo Cell

Note: To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.