

Item#: 42319/52319 LED PLUG & GO™ LINEAR T8 REPLACEMENT LAMPS (PLUG AND PLAY)(UL

FEATURES


TYPE A)

Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

PLUG & GOTM - WORKS WITH EXISTING ELECTRONIC BALLAST*

- Exceptional efficacy
- No flickering
- ETL Sanitation Listed (NSF-2)
- *Suitable for emergency ballasts.

LIGHT DISTRIBUTION CURVE



ELECTRICAL	LAMP	DLC * System powe
Wattage	9W	12W
Voltage	120-277V	
Power Factor	0.9	
Total Harmonic Distortion (THD)	13.3	
LIGHTING PERFORMANCE		
Lumens	1475	
Lumens Per Watt (LPW)	123	
Color Temperature (сст)	4000K / 5000K	
Color Rendering (CRI)	83	
R9 (Red Value)	2	
R13 (Skin Tones)	81	
Beam Angle	160°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1	
Dimmable Lighting Control	Compatible with select dimming ballasts.	
ENVIRONMENT		
Operating Temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Samsung 1228	
CONSTRUCTION		
Housing	Glass / Plastic End Caps	
Lens	Frosted	
Base / Power Supply	G13 - Medium Bi Pin	
QUALIFICATIONS		


ENTIFIED CEEN

Visit www.designlights.org/search to confirm qualification. • DLC lists the wattage of the system power. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **42319** / **52319 LED PLUG & G0™ LINEAR T8**

DIMENSIONS (Inches)

,	
Length (MOL)	24"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768028536	50.2" x 7.3" x 7.3"	16.5
Individual Box	1	811768028539		0.66
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
91324	LED 2FT 9WT8/40K/TYPE A - CEE/DLC °	25