

User Manual Ultra-Bright LED G25 Bulb

SKU: G25_HO



support@sunco.com (844) 334-9938



Safety Information

To reduce the risk of fire, electric shock, or physical injury:

- Turn off power before changing lamp.
- Not suitable for use in fully enclosed luminaires.
- Suitable for use in Damp environment at temperatures ranging from 4°F-104°F
- Not for use where directly exposed to water.
- Not intended for use with emergency fixtures.
- Not compatible with all dimmers. For more information, please visit www.sunco.com.

This device complies with Part 15 of the FCC rules. Operation is subject to the following two conditions: 1.) This device may not cause harmful interference.

- · Not compatible with timing devices.
- All electrical connections must be in accordance with local and National Electric Code (N.E.C.) standards.
- Please review installation manual carefully before proceeding.
 Consult a qualified electrician if you are unfamiliar with proper electrical wiring connections.

WARNING:

Cancer & Reproductive Harmwww.P65Warnings.ca.gov


2.) This device must accept any interference that may cause undesired operation. Please review all instructions carefully prior to installation.

Scan for the full compatible dimmer list! **Recommended Dimmers** Brand Model Lutron AYCI -153P-WH P-PKG1W-WH-R Lutron CTCL-153PDH-WH Lutron DVCI -153P-WH Lutron Leviton DSL06-001-1LZ IPL06-011-10Z Leviton RDL06-001-10Z Leviton Leviton NO.6674 600W

Specifications

Voltage	120V	Lifetime	15,000 hrs
Wattage	11W	Lumens	1000LM
Wattage Equiv.	100W	Moisture Rating	Damp
Beam Angle	320°	CRI	80+
Frequency	60Hz	Usage	Indoor
Housing Material	PA+PC	Amps	125mA
Dimmable	Yes	Warranty	5 Years

Light Distribution Angle



Lighting distribution angle refers to how light spread from light source and plays crucial role in choosing the right fixture or bulb. Symmetric lighting distribution emits light uniformly in all directions, forming a cone-shaped pattern that offers widespread illumination

Asymmetric lighting distribution. also known as beam angle, focuses light in specific direction. Keep in mind that factors like reflector design, lens type, and distance between the light source and the illuminated

2071°

surface can influence the lighting distribution angle.

Need help? Our troubleshooting	Contact us for expert assistance
section is here to help.	and brighten your day!

Installation Bulb isn't turning on.	Verify bulb is properly connected circuit breaker hasn't tripped.
Burn Out	
Bulb unexpectedly fails.	Reach out to customer support.
Dimming	
Bulb not dimming properly.	Verify dimmer compatibility.
Flickering	
Bulbs flickering on same circuit.	Verify bulbs not overloading circuit.
Buzzing Bulbs emitting buzzing noise.	Verify bulb compatibility with fixture and voltage rating.

Warranty Policy

Industry leading 5-year warranty. Scan the QR code for 2 extra years of protection!



30 Day Return

At Sunco we value our customers and stand by the quality of our products. If you are not satisfied with your purchase, returns are accepted within 30 days of purchase date.

Customer Service

Los Angeles lighting experts ready to assist you! Contact us at:

Email:

support@sunco.com

Call or Text: (844) 334-9938