2x4 Retrofit CenterBasket Troffer

Sunco's state-of-the-art retrofit troffer is the perfect lighting solution for commercial and industrial spaces. Installation is quick and hassle-free, and our troffers are compatible with various control systems, allowing you to customize the lighting experience to suit your specific needs.


MODELS

PN24_RTR_DU-WH-3550K-1PK



LIGHT DISTRIBUTION ANGLE

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



 $NOTE: The \ curves \ indicate \ the \ illuminated \ area \ and \ the \ average \ illumination \ at \ different \ distances.$

CERTIFICATIONS









SPECIFICATIONS

| Voltage | AC120-277V |
|--------------|------------|
| Wattage | 30/40/50W |
| Power Factor | >0.9 |

LIGHTING PERFORMANCE

| Lumens | 3500K: 3900/5200/6500LM 4000K: 4200/5600/7000LM 5000K: 4050/5400/6750LM |
|----------------|---|
| CRI | 80 |
| Beam Angle | 120° |
| Dimmable | 0-10V |
| Efficacy | 130LM/W for 3500K 135LM/W for 4000K 140LM/W for 5000K |
| Frequency | 50/60HZ |
| Selectable CCT | 3500K,4000K,5000K |
| | |

ENVIRONMENT

| Operating Temperature | -4°F - 113°F |
|-----------------------|---------------|
| Moisture Rating | Damp Location |

CONSTRUCTION

| Housing Material | SPCC+PC |
|------------------|----------|
| Weight | 7.95 lbs |

LIFETIME

| Average Lifetime | 50000 Hrs |
|------------------|-----------|
| Warranty | 7 Years |