

Item#: 03688 **LED VAPOR TIGHT JELLY JAR**

DIRECT AMBIENT LUMINARIES

FEATURES

- Use 80% less energy than traditional fixtures
- · Frosted diffuser provides even light distribution
- Sturdy cast iron cage protects globe from damage
- Built in surge protection

APPLICATION

Ideal for entryways, warehouses, construction sites, industrial and retail locations, or harsh environments.

ELECTRICAL

Wattage	14W
Voltage	100-277V
Current	0.17A
Power Factor	0.9
Total Harmonic Distortion (THD)	<15
LIGHTING PERFORMANCE	

Lumens	900
Lumens Per Watt (LPW)	64
Color Temperature (CCT)	4000K
Color Rendering (CRI)	80
R9 (Red Value)	-1
R13 (Skin Tones)	80
Beam Angle	150°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	Aut Children La

ENVIRONMENT

Operating Temperature	-13° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Opto 2835W	
Driver	886326	

CONSTRUCTION

Housing	Cast Iron	
Lens	Glass	
Base / Power Supply	Hard Wired	
Finish	Grey Powder Coated	

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: 03688 LED VAPOR TIGHT JELLY JAR

DIMENSIONS (Inches)
--------------	---------

Length (MOL)	10.8"
Width/Diameter (MOD)	5.6"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)

COLL CHILLIA DOCUMENTO (Gro)	mor aranabio ar timo timoi,
Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768024859	20.1" x 11.4" x 11"	17.4
Individual Box	1	811768024852		4.4
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
03688	LED VAPOR TIGHT GLASS JELLY JAR/14W/40K/FR/100-277V/CEILING MOUNT	4