



**SELECTABLE
WATTAGE**

Item#: **11755**
LED 2' POWER-SELECT™
LINEAR HIGH BAY
 HIGH-BAY LUMINAIRES FOR COMMERCIAL AND
 INDUSTRIAL BUILDINGS

FEATURES

- Selectable wattage
- High lumen output - bright and high lumen per watt.
- Integrated LED - maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle - uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.
- Pre-installed sensor socket.

MOUNTING

Designed for suspended or pendent mounting.
(V-hooks & 41.3" chains included)

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	58W / 78W / 92W
Voltage	120-277V
Current	92W = 0.76A @ 120V
Power Factor	0.9
Total Harmonic Distortion (THD)	7.2

LIGHTING PERFORMANCE

Lumens	8758 / 11778 / 13892
Lumens Per Watt (LPW)	151
Color Temperature (CCT)	5000K
Color Rendering (CRI)	78
R9 (Red Value)	-20
R13 (Skin Tones)	78
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B3 - U2 - G1
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Bridgelux
Driver	SIL80-I2000 DS

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS




Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **11755**
LED 2' POWER-SELECT™ LINEAR HIGH BAY

DIMENSIONS (Inches)

Length	24.8"
Width	15"
Height	2.2"
Net Weight (Lbs)	10.4
Chain Length	41.3" (2 ea.)



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING

PACKAGING	UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)	
Master Carton	1	811768024760	25.6" x 15.3" x 2.4"	--
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
11755	LED 2FT POWER-SELECT™ LINEAR HL HIGH BAY/58-78-92W/50K/DIMM/120-277V - DLC ®	1

ACCESSORIES

91255	PENDENT MOUNT FOR HL HIGH BAY	25
80755	PHOTO/MICROWAVE BI-LEVEL DIMMING SENSOR FOR POWER-SELECT™ HB	56
90755	REMOTE CONTROL FOR PHOTO/MICROWAVE MOTION SENSOR	150
91355	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
02355	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
12355	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
33555	MOUNTING PLATE/INTEGRATED EM PACK FOR HL HIGH BAYS	100
20054	100FT ROLL NO. 12 JACK CHAIN	Per Foot

ADDITIONAL INFORMATION:

Family Item(s): 01755/4000K

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.