

Item#: 23688 LED VAPOR TIGHT JELLY JAR DIRECT AMBIENT LUMINARIES

FEATURES

- Use 80% less energy than traditional fixtures
- Frosted diffuser provides even light distribution
- Sturdy cast iron cage protects globe from damage
- Built in surge protection

APPLICATION

Ideal for entryways, warehouses, construction sites, industrial and retail locations, or harsh environments.

ELECTRICAL

Wattage	14W
Voltage	100-277V
Current	0.17A
Power Factor	0.9
Total Harmonic Distortion (THD)	<15
LIGHTING PERFORMANCE	
Lumone	000

Lumens	900
Lumens Per Watt (LPW)	64
Color Temperature (CCT)	4000K
Color Rendering (CRI)	80
R9 (Red Value)	-1
R13 (Skin Tones)	81
Beam Angle	150°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	CHET CHIMARMELS

ENVIRONMENT

Operating Temperature	-13° ~ 104°F
Suitable Location	WET
Ingress Protection Rating	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Opto 2835W
Driver	886326

CONSTRUCTION

Housing	Cast Iron
Lens	Glass
Base / Power Supply	Hard Wired
Finish	Grey Powder Coated

QUALIFICATIONS




Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: 23688 LED VAPOR TIGHT JELLY JAR

DIMENSIONS (Inches)	
Length (MOL)	11.3"
Width/Diameter (MOD)	7.4"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10854432004269	22.8" x 13.8" x 10.6"	20.3
Individual Box	1	854432004262		5.1
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
23688	LED VAPOR TIGHT GLASS JELLY JAR/14W/40K/FR/100-277V/WALL MOUNT	4