



Item#: **45738**
LED CEILING LIGHT
 INDOOR FIXTURE

FEATURES

- Diffusing lens provides glare free illumination and even light distribution.
- Designed with the lasted solid state lighting and electronic driver for optimal performance and energy efficiency.
- Die formed cold rolled steel mounting plate; painted with a treatment for anti-corrosion.

APPLICATION

Homes, schools, retail, office and hospitality.

ELECTRICAL

Wattage	16W
Voltage	120V
Current	0.15A
Power Factor	0.8
Total Harmonic Distortion (THD)	N/A

LIGHTING PERFORMANCE

Lumens	1000
Lumens Per Watt (LPW)	63
Color Temperature (CCT)	4000K
Color Rendering (CRI)	80
R9 (Red Value)	23
R13 (Skin Tones)	87
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	<i>Dimmable</i> 120V Dimming

ENVIRONMENT

Operating Temperature	-4° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

LIFESPAN

Average Life (Hours)	35,000
Warranty (Years)	3

COMPONENTS

LED Light Source	Samsung SPMWHx228F
Driver	837546 - 16W320MAC

CONSTRUCTION

Housing	C.R.S / PC
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS




Visit www.energystar.gov to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **45738**
LED CEILING LIGHT

DIMENSIONS (Inches)

Width/Diameter (MOD)	11"
Height	3.6"
Net Weight (Lbs)	--



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	10	10811768025115	24.8" x 21.7" x 13"	14.6
Individual Box	1	811768025118	12" x 4.1" x 12.1"	1.5
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
83754	LED 11IN MUSHROOM CEILING LIGHT/16W/40K/DIMM/120V/WHT - ENERGY STAR®	10