

Item#: 54019
LED PLUG & GO™ LINEAR T8
REPLACEMENT LAMPS (PLUG AND PLAY)
(UL TYPE A)

FEATURES

Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

PLUG & GO™ - WORKS WITH EXISTING ELECTRONIC BALLAST*

- · Thermal fuse for added safety
- Exceptional efficacy
- No flickering
- *Not suitable for dimming or emergency ballasts.

Voltage Power Factor Total Harmonic Distortion (THD) LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	AMP POWER	
Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	2W 15W	
Total Harmonic Distortion (THD) LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	120-277V	
LUMENS LUMENS PER WATT (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	0.9	
Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION	20	
Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G		
Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	1800	
Color Rendering (CRI) R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	120	
R9 (Red Value) R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	5000K	
R13 (Skin Tones) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	82	
Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	8.6	
Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	83.1	
BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	210°	
Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	Type IV, Very Short	
ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	B1 - U1 - G1	
Operating Temperature Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	AUT DIMAGILLS	
Suitable Location Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G		
Ingress Protection Rating Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	-4° ~ 113°F	
Suitable Fixture Type LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	DAMP	
LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing	IP20	
Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G	Enclosed	
Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION Housing G		
COMPONENTS LED Light Source CONSTRUCTION Housing G	50,000	
LED Light Source CONSTRUCTION Housing G	5	
CONSTRUCTION Housing G		
Housing G	Toyoda	
Housing G		
Lens	Glass / Metal End Caps	
	Frosted	
Base / Power Supply	G13 - Medium Bi Pin	






Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Item#: **54019 LED PLUG & GO™ LINEAR T8**

DIMENSIONS (Inches)

Length (MOL)	47.8"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768026037	48.8" x 5.9" x 5.9"	14.4
Individual Box	1	811768026030		0.58
Country of Origin	China			
HS Tariff	8539.50.0050			