



Item#: **58248**LED TONE-SELECT™ PRESTIGE™ I CEILING LIGHT

INDOOR FIXTURE

FEATURES

- Selectable color temperature
- LED surface mount fixture provides glare free illumination and even light distribution with a clean, modern look.
- · Diffusing lens
- · Low profile design

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, hallways, lobbies and other residential and commercial applications.

ELECTRICAL

Wattage	21W
Voltage	120V
Current	180mA
Power Factor	0.9
Total Harmonic Distortion (THD)	

LIGHTING PERFORMANCE

Lumens	1470		
Lumens Per Watt (LPW)	70		
Color Temperature (CCT)	27K /30K / 35K / 40K / 50K		
Color Rendering (CRI)	80		
R9 (Red Value)			
R13 (Skin Tones)			
Beam Angle	220°		
Light Distribution			
Dimmable Lighting Control	Dimmable see compatibility report		

ENVIRONMENT

Operating Temperature	-4° ~ 104°F	
Suitable Location	DAMP Indoor / Covered Ceilings	
Ingress Protection Rating	IP20	

LIFESPAN

Average Life (Hours)	35,000
Warranty (Years)	3

COMPONENTS

LED Light Source	
Driver	

CONSTRUCTION

Housing	Steel
Lens	PC
Base / Power Supply	Hard Wired
Finish	White




Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: 58248 LED TONE-SELECT™ PRESTIGE™ I CEILING LIGHT

DIMENSIONS (Inches)	
Width/Diameter (MOD)	13"
Height	2.3"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
Dimmer Compatibility	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIFW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10811768023678	15.8" x 14.7" x 14.7"	13.7
Individual Box	1	811768023671	13.9" x 13.9" x 2.4"	2.3
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
58248	LED 13IN TONE-SELECT™ PRESTIGE™ I CEILING LIGHT/21W/27-30-35-40-50K/DIMM/120V/WHT	6