

Item#: **72129 LED HIGH WATTAGE 180° LAMP**

REPLACEMENT LAMPS FOR OUTDOOR POLE/ARM MOUNTED DECORATIVE LUMINAIRES (TYPE B)

FEATURES

- Environmentally friendly; uses less energy than a traditional lamp.
- 180° optical design that provides even light distribution.
- 350° rotating base for precise positioning
- · Excellent heat dissipation.
- · High lumen output.
- Only Dimmable on 120V.

APPLICATION

Replacement lamps for top post, high bays, parking lots and street lighting.

ELECTRICAL

| Wattage | 100W |
|---------------------------------|----------|
| Voltage | 120-277V |
| Current | 0.88A |
| Power Factor | 0.9 |
| Total Harmonic Distortion (THD) | 20 |
| | |

LIGHTING PERFORMANCE

| Lumens | 14800 | | |
|--|--|--|--|
| Lumens Per Watt (LPW) | 148 | | |
| Color Temperature (CCT) | 5000K | | |
| Color Rendering (CRI) | 82 | | |
| R9 (Red Value) | 5 | | |
| R13 (Skin Tones) | | | |
| Beam Angle | 110° | | |
| Light Distribution | | | |
| BUG Rating (Backlight, Uplight, and Glare) | | | |
| Dimmable Lighting Control | Dimmable see compatibility report | | |

ENVIRONMENT

| Operating Temperature | -40° ~ 149°F |
|--|--------------|
| Suitable Location | DAMP |
| Ingress Protection Rating | IP40 |
| Suitable Fixture Type | Enclosed |
| Suitable for Emergency Fixtures/Ballasts | No |
| | |

LIFESPAN

| Average Life (Hours) | 50,000 |
|----------------------|--------|
| Warranty (Years) | 5 |

COMPONENTS

LED Light Source Bridgelux

CONSTRUCTION

| Housing | Aluminum / PC | |
|---------------------|---------------|--|
| Lens | Clear | |
| Base / Power Supply | E39 - Mogul | |

QUALIFICATIONS






Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **72129 LED HIGH WATTAGE 180° LAMP**

DIMENSIONS (Inches)

| Length (MOL) | 11" |
|------------------|------|
| Width | 4.7" |
| Height | 3.1" |
| Net Weight (Lbs) | |

| SUPPORTING DOCUMENTS (Grey = not available at this time.) | | |
|--|------|--|
| Product Sheet | VIEW | |
| Install Instructions | VIEW | |
| Dimmer Compatibility | VIEW | |
| IES Download from Web Item | VIEW | |
| LM79 | VIEW | |
| LM80 | VIEW | |



| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|----------------|---------------------------|---------------------------|
| Master Carton | 4 | 10811768028901 | 25.4" x 12.4" x 4.9" | |
| Individual Box | 1 | 811768028904 | 5.9" x 4.1" x 12.3" | |
| Country of Origin | China | | | |
| HS Tariff | 8539.52.0010 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|-------|--|------|
| 72129 | LED 100W/50K/180°/DIMM/120-277V/MOG - DLC ° | 4 |